

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> W05	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 6	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> GETTYSBURG	<u>STATE</u> PA
<u>AIRPORT ELEVATION</u> 553	<u>TDZE</u> 553	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u> 11W	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 12 JUNE 2025	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
HYPER		DOAAH		TF	FO	1.00	304.13	12.42	3600
REEES	IAF	DOAAH	NOPT	TF	FB	1.00	109.11	13.73	3600
DOAAH	IF/IAF	SOOPS		TF	FB	1.00	087.41	5.00	2800
SOOPS	FAF	WIDUN/1.98 NM TO RW06		TF	FB	0.30	062.47	3.25	
WIDUN/1.98 NM TO RW06		RW06	MAP	TF	FO	0.30	062.47	1.98	
RW06	MAP	1700 MSL		CA			062.47		1700
1700 MSL		REEES		DF	FO	1.00			3600

MISSED APPROACH

MAP:

LNAV: RW06

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1700 THEN CLIMBING LEFT TURN TO 3600 DIRECT REEES AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF

(IAF)
2. HOLD W DOAAH, LT, 087.41 INBOUND, 3600 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 062.47

FAC: SOOPS

DIST FAF TO MAP: 5.22

DIST FAF TO THLD: 5.22
4. MIN ALT: DOAAH 3600, SOOPS 2800, WIDUN/1.98 NM TO RW06 1420
5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:
6. MIN GP INCPT:

GP ALT AT FAF:

OM:

MM:

IM:
7. GP ANGLE:

34:1: IS NOT CLEAR

20:1: IS NOT CLEAR

TCH:
8. MSA FROM: RW06 3600



PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: RWY 6 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 2.00 DEGREES.
CHART NOTE: USE HGR ALTIMETER SETTING
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT REEES ON T299 SOUTHWEST BOUND, AND ARRIVALS AT HYPER ON V39-143 NORTHEAST BOUND.

ADDITIONAL FLIGHT DATA:

CHART HGR ASOS-3
SOOPS TO RW06:4.00/40
HOLD W, RT, 109.11 INBOUND.
FAS OBST: 837 AAO 394924N/0771900W.
1552 AAO 394900N/0772339W, 1011 AAO 394921N/0771927W.
CHART P-40/R-4009.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	1160	1	607	1160	1	607		NA			NA				
CIRCLING	1180	1	627	1260	1	707		NA			NA				

CHANGES - REASONS

ORIGINAL PROCEDURE.

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZDC, PAX APP CON, AMGR

FLIGHT CHECKED BY

NATHAN J CHOTT

Digitally signed by
ROBERT G HAMILTON
Mar 25, 2025

OFFICE

AJF

DATE

03/20/2025

DEVELOPED BY

WESTLEY OWENS

Digitally signed by
ROBERT G HAMILTON
Mar 25, 2025

OFFICE

AJV-A431

DATE

10/04/2024

APPROVED BY

ERIC N SUSKI

Digitally signed by
ROBERT G HAMILTON
Mar 25, 2025

OFFICE

AJV-A431

DATE

TITLE
MANAGER

