FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT AIRPORT ID DENVER INTL KDEN			PROCEDURE NAME RNAV (RNP) Z RWY 26			<u>(</u>	DRIGINAL/AMENDMENT 1	<u>CITY</u> DENVER	STATE CO
AIRPORT ELEVATION 5434	<u>TDZ</u> 530		SUPERSEDED RNAV (RNP) Z RWY 26				L <mark>/AMENDMENT</mark> DATED DRIG-A 12/11/2014	MAG VAR 8E	EPOCH YEAR 2015
FACILITY RNAV	COORDINATES OF		ACTUAL EFFECTIVE DATE 26 MARCH 2020			RED EFF ROUT	ECTIVE DATE CANCEL	<u>USPEND</u>	
TERMINAL ROUTES									
FROM	FIX TYPE	<u>T0</u>	FIX TYPE	LEG TYPE	FO/FB	<u>RNP</u>	COURSE	DISTANCE	ALTITUDE
CAPTJ	IF	BCALN		TF	FB	1.00	082.50	3.28	10000
BCALN		JPBAG		RF	FB	1.00	(2.77 NM RADIUS CW (CFSDC))	8.72	7300
JIBAT	IF	HOTDG		TF	FB	1.00	081.66	3.28	10000
HOTDG		JPBAG		RF	FB	1.00	(2.80 NM RADIUS CCW (CFTSP)	8.75	7300
FUZZZ	IF	JPBAG		TF	FB	1.00	262.72	5.76	7300
JPBAG		GRASP	PFAF	TF	FB	1.00	262.64	1.11	7000
GRASP	PFAF	DA	MAP	TF	FO	0.30	262.62	5.18	
DA	MAP	6000 MSL		CA			262.62		6000
6000 MSL		NIWOT		DF	FO	1.00			10000

MISSED APPROACH

MAP:

RNP: DA

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 6000 THEN CLIMBING RIGHT TURN TO 10000 DIRECT NIWOT AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

AIRPORT DENVER INTL	<u>AIRPORT I</u> KDEN		PROCEDURE NAME RNAV (RNP) Z RWY 26	ORIGINAL/AMENDMENT 1	<u>CITY</u> DENVER	STATE CO
PROFILE:						
1. PT SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF (IAF)			
2. PROFILE STARTS AT GRASP						
3. FAC: 262.62 PFAF: GRASE 4. MIN ALT: GRASP 7000	D	DIST PFAF TO MAP	: DIST PF	AF TO THLD:		
5. DIST TO THLD FROM OM: 5.18	MM:	IM: 150 HAT:	257 HAT: 0.68	GS ANT:		
6. MIN GP INCPT: 7000	GP ALT AT PFAF : GRA	ASP 7000	OM:	MM:	IM:	
7. GP ANGLE: 3.00	34:1: IS CLEAR	20:1: IS CLEAR	TCH: 55.1			
8. MSA FROM: RW26 8100						

PBN REQUIREMENTS NOTE:

RNP AR APCH.

NOTES:

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -23°C OR ABOVE 54°C. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.15 ALL CATS VISIBILITY TO RVR 4000, AND INCREASE RNP 0.30 ALL CATS VISIBILITY TO RVR 4500. CHART SPEED ICON IN PLANVIEW AT CAPTJ : AT 210 KIAS. CHART PLANVIEW NOTE ADJACENT TO CAPTJ IF: RF REQUIRED. CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS

ADDITIONAL FLIGHT DATA:

CHART MANDATORY 11000 AT JIBAT CHART MANDATORY 11000 AT CAPTJ HOLD SE, RT, 314.00 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA

STANDARD

CATEGORY:	Α		В		С		D			E					
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
						AUTHC	RIZATION F	REQUIRED							
RNP 0.15 DA	5566	2400	257	5566	2400	257	5566	2400	257	5566	2400	257		OUALIT_	
RNP 0.30 DA	5611	2400	302	5611	2400	302	5611	2400	302	5611	2400	302		24	
														CHECKE	

<u>AIRPORT</u> DENVER INTL	AIRPORT ID KDEN	PROCEDURE NAME RNAV (RNP) Z RWY 26	ORIGINAL/AMENDMENT 1	<u>CITY</u> DENVER	STATE CO
CHANGES - REASONS					

1. ADDED PBN REQUIREMENTS NOTE RNP AR APCH. - ADDED IAW 8260.58A CHNG 2 TABLE 1-2-1.

2. REMOVED PLAINVIEW NOTE AT ELREY: MAX 210 KIAS AND PLANVIEW NOTE ADJACENT TO ELREY IAF: RF REQUIRED. - ELREY FIX REMOVED FROM PROCEDURE.

3. ADDED PLANVIEW NOTE AT JIBAT: AT 210 KIAS AND ADDED PLANIVEW NOTE ADJACENT TO JIBAT: RF REQUIRED. - FIX JIBAT ADDED TO PROCEDURE.

4.UPDATED PROFILE NOTE FROM "VGSI AND RNAV GLIDEPATH NOT COINCIDENT" TO VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). - UPDATED IAW 8260.19G PARA 8-6-9(M)1.

5. REMOVED ROUTE TYPE QUALIFIER INFORMATION FROM ADDITIONAL FLIGHT DATA. - DATA NO LONGER REQUIRED.

6. FIXES ZLOGR, ZNOBL, AND FMSDT REMOVED FROM PROCEDURE. - PER DENVER METROPLEX RNP FILE AND IFP CHECKLIST.

7. RNP 0.10 DA UPDATED TO RNP 0.15 DA PER CRITERIA AND DA/HAT UPDATED FROM 5570/261 TO DA/HAT 5566/257. - RNP 0.10 LINE OF MINIMA NO LONGER PUBLISHED AND NEW CONTROLLING OBSTRUCTION IDENTIFIED.

8. RNP 0.30 DA/HAT CHANGED FROM 5668/359 TO 5611/302. - NEW CONTROLLING OBSTRUCTION IDENTIFIED.

9. REMOVED PLANVIEW NOTE AT BCALN: MAX 210 KIAS. - SPEED RESTRICTIONS NO LONGER UTILIZED.

10. RNP 0.30 VISIBILITY ALL CATS CHANGED FROM RVR 4000 TO RVR 2400. - UPDATED IAW APPROVED VISI TOOL.

11. REMOVED NOTE GPS REQUIRED. - NOTE NO LONGER REQUIRED.

12. REMOVED NOTE USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE DURING SIMULTANEOUS OPERATIONS. - NOTE NO LONGER LISTED IN CRITERIA.

13. NOTE SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 25, EXCEPT FOR ARRIVALS AT CAPTJ AND ELREY CHANGED TO SIMULTANEOUS APPROACH AUTHORIZED. - NOTE UPDATED IAW 8260.19H PARA 8-6-1108.

14. CHANGED NOTE "FOR INOPERATIVE MALSR, INCREASE RNP 0.10 ALL CATS VISIBILITY TO RVR 4500 AND RNP 0.30 ALL CATS VISIBILITY TO RVR 6000" TO "FOR INOPERATIVE ALS, INCREASE RNP 0.15 ALL CATS VISIBILITY TO RVR 4000, AND INCREASE RNP 0.30 ALL CATS VISIBILITY TO RVR 4500".

15. CHANGE PLANVIEW NOTE AT CAPTJ: MAX 210 KIAS TO CHART SPEED ICON IN PLANVIEW AT CAPTJ: AT 210 KIAS. - UPDATED IAW 8260.19H PARA 4-6-10G.

16. ADDED FIX HOTDG TO PROCEDURE. - PER DENVER METROPLEX MASTER RNP FILE AND IFP CHECKLIST.

17. REMOVED CHARTING OF LOC RWY 25 FROM ADDITIONAL FLIGHT DATA. - CHARTING OF THE LOC IS NO LONGER REQUIRED IAW 8260.19H .

18. CHANGED FROM DISTANCE TO THLD 261 HATH TO 257 HAT. - LOWERED HAT DUE TO NEW CONTROLLING OBSTRUCTION.

COORDINATED WITH:

A4A 🗙 ALPA 🗙	AOPA X APA X	hai 🗌	NBAA 🗙	OTHER: ZDV, DEN ATCT, DEN APP CON, AMGR		
FLIGHT CHECKED BY	Digitally signed by DONALD H LANIER Jan 28, 2020			<u>OFFICE</u> FICO	DATE 1/25/20	
JAMES HAWLEY DEVELOPED BY NICHOLAS K. JACKSON	Digitally signed by			<u>OFFICE</u> AJV-A431	DATE 10/16/2019	
APPROVED BY GEORGE DAVIS	Dec 12, 2019 Digitally signed by DONALD H LANIER			<u>OFFICE</u> AJV-A450	DATE	<u>TITLE</u> MANAGER

Jan 28, 2020