

**Federal Aviation  
Administration**

**Transmittal Letter 21-26**

**October 29, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

| AIRAC DATE | STATE | CITY      | AIRPORT       | FDC NUMBER | FDC DATE   | SUBJECT                      |
|------------|-------|-----------|---------------|------------|------------|------------------------------|
| 12/2/2021  | IN    | Rochester | Fulton County | 1/4148     | 10/19/2021 | RNAV (GPS) RWY<br>29, Amdt 1 |

**AIRAC Date: 2 DECEMBER 2021**

FDC 1/4148 RCR IAP FULTON COUNTY, ROCHESTER, IN. RNAV (GPS) RWY 29, AMDT 1...  
CIRCLING CAT C MDA 1480/HAA 690, CAT D MDA 1620/HAA 830, VIS CAT C 2, CAT D 2 3/4.  
ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2 3/4; NA WHEN LOCAL  
WEATHER NOT AVAILABLE. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER  
SETTING NOT RECEIVED, USE GOSHEN ALTIMETER SETTING: INCREASE LPV DA TO  
1208 FEET AND VISIBILITY ALL CATS 1/4 SM; INCREASE LNAV/VNAV DA TO 1325 AND  
VISIBILITY ALL CATS 1/2 SM; INCREASE ALL MDA 100 FEET AND VISIBILITY LNAV CATS C  
AND D AND CIRCLING CATS C AND D 1/4 SM. THIS IS RNAV (GPS) RWY 29, AMDT 1A.  
2109281437-PERM