

**Federal Aviation  
Administration**

**Transmittal Letter 20-15**

**May 29, 2020**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/16/2020	SC	Myrtle Beach	Myrtle Beach Intl	0/9472	5/14/2020	RNAV (GPS) RWY 36, Amdt 4

**AIRAC Date: 16 JULY 2020**

FDC 0/9472 MYR IAP MYRTLE BEACH INTL, MYRTLE BEACH, SC. RNAV (GPS) RWY 36, AMDT 4...  
DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F).  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE NOTE: FOR INOPERATIVE MALSF, INCREASE LNAV/VNAV CATS D/E VISIBILITY TO RVR 6000, AND LNAV CATS D/E VISIBILITY TO 1 1/4. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV CATS D/E VISIBILITY TO RVR 6000, AND LNAV CATS C/D/E VISIBILITY TO 1 3/8 SM. LNAV ALL CATS MDA/HAT 480/455. DELETE NOTE: RADAR REQUIRED. THIS IS RNAV (GPS) RWY 36, AMDT 4A. 2005081700-PERM