

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW09
SALFE (IF/IAF)	FASTI (FB)	089.44 / 6.42	2200	CLIMB TO 2500 DIRECT KUKAF AND HOLD.
FASTI (FAF)	CAGSA/3.40 NM TO RW09	089.53 / 1.53	2500	
CAGSA/3.40 NM TO RW09	RW09 (MAP) (FO)	089.53 / 3.40		
RW09 (MAP)	990 MSL	089.53		
990 MSL	KUKAF (FO)			ADDITIONAL FLIGHT DATA: HOLD E, RT, 269.74 INBOUND. CHART FAS OBST: 825 TOWER 413045N/0825624W CHART RESTRICTED AREA 5502 A/B. FASTI TO RW09: 3.00/40. CHART CIRCLING ICON.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD W SALFE, RT, 089.44 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
3. FAC: 089.53 FAF: FASTI DIST FAF TO MAP: 4.93 THLD: 4.93
4. MIN. ALT: SALFE 3000, FASTI 2200, CAGSA/3.40 NM TO RW09 1720
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW09 3100

MAG VAR: 7W EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1140	1	550	1140	1	550	1140	1 5/8	550	1140	1 5/8	550			
CIRCLING	1140	1	550	1140	1	550	1180	1 5/8	590	1580	3	990			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT SALFE ON V426 SOUTHBOUND.
 CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: NIGHT LANDING: RWY 9, 18, 36 NA.
 (SEE FORM 8260-10)

@ CAT D 1000-3
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE PORT CLINTON, OH	ELEVATION: 590 TDZE: 590 AIRPORT NAME: CARL R KELLER FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 5 MARCH 2015	SUP: CHECKED AMDT: ORIG DATED: 07/02/2009
------------------------------------	---	------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOLEDO EXECUTIVE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND ALL CAT C/D VISIBILITIES 1/4 MILE.



CITY AND STATE PORT CLINTON, OH	ELEVATION: 590 TDZE: 590 AIRPORT NAME: CARL R KELLER FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 5 MARCH 2015	SUP:
				AMDT: ORIG
				DATED: 07/02/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	SALFE	SALFE	010	IAF	HF	R	FO		089.4(082.4T)	004.0	AA 03000	
		SALFE	010	FACF	IF		FB				AA 03000	
		FASTI	020	FAF	TF		FB	0.5	089.4(082.4T)	006.4	AA 02200	
		CAGSA	021	SDF	TF		FB	0.3	089.5(082.5T)	001.5	AA 01720	GS 01737
		RW09	030	MAP	TF		FO	0.3	089.5(082.5T)	003.4	AT 00629	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		089.5(082.5T)		AA 00990	
	KUKAF	050		DF		FO				AA 02500	
	KUKAF	060		HM	R	FO		269.7(262.7T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CAGSA	N413031.32	W0825723.27	N4130.522	W08257.388
	FASTI	N413019.37	W0825924.72	N4130.323	W08259.412
	KUKAF	N413217.05	W0823913.90	N4132.284	W08239.232
	SALFE	N412928.98	W0830752.60	N4129.483	W08307.877
	RW09	N413057.70	W0825254.00	N4130.962	W08252.900

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW09	00589	40



CITY AND STATE PORT CLINTON, OH	ELEVATION: 590	TDZE: 590	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: CARL R KELLER FIELD		RNAV	RNAV (GPS) RWY 9, AMDT 1	AMDT: ORIG
				5 MARCH 2015	DATED: 07/02/2009