

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW07 LNAV: RW07					
JEFFY (IAF)		YUGKU (TF) (FB) (RNP 1.00)		106.54 / 5.30				7100		CLIMBING RIGHT TURN TO 7000 DIRECT IMSIJ AND HOLD.					
YUGKU		RGAMI/RADAR (TF) (FB) (RNP 1.00)		106.60 / 6.61				7000							
RGAMI/RADAR (IF)		HIVYU (TF) (FB) (RNP 1.00)		092.02 / 3.00				6200							
HIVYU		JITLA (TF) (FB) (RNP 1.00)		092.06 / 3.00				5500							
JITLA (FAF)		UWEJO/5.00 NM TO RW07 (TF) (FB) (RNP 0.30)		077.09 / 2.83						ADDITIONAL FLIGHT DATA: HOLD E, LT, 276.00 INBOUND. CHART FAS OBST: 2659 TREE 343713N/1180810W, 2629 TREE 343737N/1180808W. 4022 AAO 343722N/1181549W. 4089 AAO 343738N/1181633W. 2649 TREE 343734N/1180831W. CHART VDP AT 0.78 NM TO RW07. WAAS CHANNEL # 53441 REFERENCE PATH ID: W07A CHART CIRCLING ICON. ZENAB TO RW7: 3.50/50. CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 3.00 DEGREES. LTP HAE: 742.9 M					
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 12E EPOCH YEAR: 2020					
2. PROFILE STARTS AT JEFFY															
3. FAC: 077.09 FAF: JITLA DIST FAF TO MAP: 7.83 THLD: 7.83															
4. MIN. ALT: JEFFY 8000, YUGKU 7100, RGAMI 7000, HIVYU 6200, JITLA 5500, UWEJO/5.00 NM TO RW07 4440, (SEE FORM 8260-10)															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS CLEAR															
8. MSA FROM: RW07 10600															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY >>>>>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	2880	1	340	2880	1	340	2880	1	340	2880	1	340			
LNAV MDA	2920	1	380	2920	1	380	2920	1	380	2920	1	380			
CIRCLING	3020	1	477	3060	1	517	3140	1 1/2	597	3740	3	1197			
NOTES: CHART NOTE: CIRCLING NA FOR CATS C AND D SOUTH OF RWYS 4 AND 25. @ CAT D 1200-3 CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JEFFY ON V165-459 AND V137 NORTHWEST BOUND. CHART PLANVIEW NOTE: CAUTION: HIGH TERRAIN 5 NM SW OF AIRPORT.															
CITY AND STATE PALMDALE, CA		ELEVATION: 2543 TDZE: 2540 AIRPORT NAME: PALMDALE USAF PLANT 42		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 24 MAY 2018					SUP: AMDT: NONE DATED				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

LINE 4, (CONT.):
 ZENAB/1.60 NM TO RW07 3180

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
UWEJO/5.00 NM TO RW07	ZENAB/1.60 NM TO RW07 (TF) (FB) (RNP 0.30)	077.09 / 3.40	
ZENAB/1.60 NM TO RW07	RW07 (MAP) (TF) (FO) (RNP 0.30)	077.09 / 1.60	
RW07 (MAP)	2880 MSL (CA)		
2880 MSL	IMSIJ (DF) (FO) (RNP 1.00)		7000

QUALITY
19
CHECKED

CITY AND STATE PALMDALE, CA	ELEVATION: 2543	TDZE: 2540	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 24 MAY 2018	SUP:
	AIRPORT NAME:				AMDT: NONE
	PALMDALE USAF PLANT 42				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPMD
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	343750.1060N
LTP/FTP LONGITUDE	1180647.0290W
LTP/FTP ELLIPSOIDAL HEIGHT	+07429
FPAP LATITUDE	343751.3700N
FPAP LONGITUDE	1180459.0665W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.50
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

4FE0997B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+07743
FPAP ORTHOMETRIC HEIGHT	+07743

QUALITY
19
CHECKED

CITY AND STATE

PALMDALE, CA

ELEVATION: 2543

TDZE: 2540

AIRPORT NAME:

PALMDALE USAF PLANT 42

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, ORIG

24 MAY 2018

SUP:

AMDT:

NONE

DATED: