

**Federal Aviation
Administration**

Transmittal Letter 19-13

MAY 3, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/20/2019	VA	Dublin	New River Valley	9/7889	4/16/2019	RNAV (GPS) RWY 24, Amdt 1

AIRAC Date: 20 JUNE 2019

FDC 9/7889 PSK IAP NEW RIVER VALLEY, Dublin, VA. RNAV (GPS) RWY 24, AMDT 1... DELETE NOTE:
VISIBILITY REDUCTION BY HELICOPTERS NA. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS
NOTE: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -
19C (-2F) OR ABOVE 45C (113F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV
NA BELOW -19C OR ABOVE 45C. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
BLACKSBURG ALTIMETER SETTING AND INCREASE ALL DA 36 FEET, AND ALL MDA 40 FEET; INCREASE
LNAV/VNAV ALL CATS. AND LNAV CAT. C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE BLACKSBURG ALTIMETER SETTING AND INCREASE ALL DA 36 FEET, AND
ALL MDA 40 FEET; INCREASE LNAV/VNAV ALL CATS. AND LNAV CAT. C VISIBILITY 1/4 SM. DELETE
PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ROA VORTAC VIA V260 SOUTHEAST BOUND. CHART
PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ROA VORTAC ON V260 SOUTHEAST BOUND. THIS IS
RNAV (GPS) RWY 24, AMDT 1A. 1904051400-PERM