

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
WAGIR (IAF)	CARYL (NOPT) (FB)	217.90 / 6.00	2000
KOVEC (IAF)	CARYL (NOPT) (FB)	037.82 / 6.00	2000
CARYL (IF/IAF)	MAYBN (FB)	127.86 / 6.10	1600

LPV: DA
LNAV/VNAV: DA
LNAV: RW13

CLIMB TO 2000 DIRECT JURAD AND ON TRACK 075.59 TO RODDI AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 218.18 INBOUND.
CHART IN PLANVIEW: MAXIMUM HOLDING AIRSPEED 230 KIAS AT RODDI
CHART FAS OBST: 264 AAO 392915N/0743934W
CHART R-5002.
DISTANCE TO THLD FROM 200 HAT: 0.45 NM.
CHART VDP AT 1.18 MILES TO RW13*
*LNAV ONLY.
WAAS CHANNEL # 45513
REFERENCE PATH ID: W13A
CHART: ASR

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD NW CARYL, RT, 127.86 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
- FAC: 127.93 FAF: MAYBN DIST FAF TO MAP: 4.55 THLD: 4.55
- MIN. ALT: CARYL 2000, MAYBN 1600
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 1600 GS ALT AT: MAYBN 1600 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 58.4 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 10W

EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	STANDARD @							
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	275	2400	200	275	2400	200	275	2400	200	275	2400	200	275	2400	200
LNAV/VNAV DA	475	4000	400	475	4000	400	475	4000	400	475	4000	400	475	5000	400
LNAV MDA	520	2400	445	520	2400	445	520	4000	445	520	5000	445	520	5000	445
CIRCLING	540	1	465	540	1	465	540	1 1/2	465	640	2	565	760	2 1/2	685

NOTES:
CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LPV CAT E VISIBILITY TO RVR 4000, LNAV/VNAV CAT E VISIBILITY TO 1 1/2, AND LNAV CAT D VISIBILITY TO RVR 6000, CAT E VISIBILITY TO 1 1/2.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

@ CAT E 800-2 1/2

QUALITY
6
CHECKED

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75 TDZE: 75 AIRPORT NAME: ATLANTIC CITY INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 4 23 SEP 2010	SUP: RNAV (GPS) RWY 13 AMDT: 3 DATED 09/25/2008
-------------------------------------	---	---------------------------------	--	---

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	038/30 CW 218/30 (NOPT)	038/8 CW 218/8	2100
2.	038/8 CW 218/8	CARYL (IF/IAF) (FB)	2000
3.	218/30 CW 308/30	218/15 CW 308/15	2100
4.	218/15 CW 308/15	WAGIR (IAF) (FB)	2000
5.	308/30 CW 038/30	308/26 CW 038/26	5500
6.	308/26 CW 038/26	KOVEC (IAF) (FB)	2000

QUALITY
6
CHECKED

CITY AND STATE
ATLANTIC CITY, NJ

ELEVATION: 75 TDZE: 75
 AIRPORT NAME:
 ATLANTIC CITY INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) Y RWY 13, AMDT 4
 23 SEP 2010

SUP: RNAV (GPS) RWY 13
 AMDT: 3
 DATED: 09/25/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KACY
RUNWAY RW13
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR Y
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W13A
LTP/FTP LATITUDE 392751.3400N
LTP/FTP LONGITUDE 0743527.6500W
LTP/FTP ELLIPSOIDAL HEIGHT -00110
FPAP LATITUDE 392704.7100N
FPAP LONGITUDE 0743334.5200W
THRESHOLD CROSSING HEIGHT (TCH) 00058.4
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0016
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

7D752283

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +00227
FPAP ORTHOMETRIC HEIGHT +00227

QUALITY
CHECKED

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75 AIRPORT NAME: ATLANTIC CITY INTL	TDZE: 75	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 4 23 SEP 2010	SUP: RNAV (GPS) RWY 13 AMDT: 3 DATED: 09/25/2008
-------------------------------------	--	----------	---------------------------------	--	--

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75	TDZE: 75	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 13
	AIRPORT NAME:			RNAV (GPS) Y RWY 13, AMDT 4	AMDT: 3
	ATLANTIC CITY INTL			23 SEP 2010	DATED: 09/25/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75 AIRPORT NAME: ATLANTIC CITY INTL	TDZE: 75	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 4 23 SEP 2010	SUP: RNAV (GPS) RWY 13
					AMDT: 3
					DATED: 09/25/2008