

**Federal Aviation
Administration**

Transmittal Letter 20-10

March 20, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	LA	Lafayette	Lafayette Rgnl/Paul Fournet Field	0/4525	3/10/2020	VOR/DME RWY 11, Amdt 1F

AIRAC Date: 23 APRIL 2020

FDC 0/4525 LFT IAP LAFAYETTE RGNL/PAUL FOURNET FIELD, LAFAYETTE, LA. VOR/DME RWY 11, AMDT 1F... CHART CIRCLING ICON. CIRCLING CAT C/D MDA 700/HAA 658. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ACADIANA RGNL ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ACADIANA RGNL ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET, INCREASE CIRCLING VISIBILITY CAT C/D 1/4 SM. THIS IS VOR/DME RWY 11, AMDT 1G. 2003091657-PERM