

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> GUM/PGUM	<u>PROCEDURE NAME</u> RNAV (GPS) Y RWY 24R	<u>ORIGINAL/AMENDMENT</u> 2C	<u>CITY</u> TAMUNING	<u>STATE</u> GU
<u>AIRPORT ELEVATION</u> 305	<u>TDZE</u> 305	<u>SUPERSEDED</u> RNAV (GPS) Y RWY 24R	<u>ORIGINAL/AMENDMENT</u> 2B	<u>DATED</u> 01/25/2024
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 2 OCTOBER 2025	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 2E
				<u>EPOCH YEAR</u> 2000
				<u>CANCEL/SUSPEND</u>

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
UNZ VORTAC		WABOX		TF	FO	1.00	062.73	16.96	3000
CULPS		HAGIX		TF	FB	1.00	185.15	16.28	3000
GUMGE		FAPAM		TF	FB	1.00	337.43	21.60	3000
HAGIX	IAF	WABOX	NOPT	TF	FB	1.00	152.98	10.00	3000
FAPAM	IAF	WABOX	NOPT	TF	FB	1.00	333.02	10.00	3000
BAGBE	IAF	WABOX	NOPT	TF	FB	1.00	253.05	18.18	3000
WABOX	IF/IAF	PAVYI		TF	FB	1.00	243.00	5.82	2300
PAVYI	FAF	RW24R	MAP	TF	FO	0.30	242.98	6.03	
RW24R	MAP	705 MSL		CA			242.98		
705 MSL		OBALE		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW24R

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT OBALE AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF

(IAF)
2. HOLD NE WABOX, RT, 243.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.
3. FAC: 242.98

FAF: PAVYI

DIST FAF TO MAP: 6.03

DIST FAF TO THLD: 6.03
4. MIN ALT: WABOX 3000, PAVYI 2300
5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:
6. MIN GP INCPT:

GP ALT AT FAF:
7. GP ANGLE:

34:1: IS NOT CLEAR

20:1: IS CLEAR

TCH:

OM:

MM:

IM:
8. MSA FROM: RW24R 2600



PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: CIRCLING NA SOUTHEAST OF RWY 6R-24L.
CHART NOTE: RWY 24R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CULPS ON A221 NORTHEAST BOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BAGBE ON A450 NORTHEAST BOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GUMGE ON R584-G205-A597 SOUTHEAST BOUND.

ADDITIONAL FLIGHT DATA:

HOLD SW, RT, 062.91 INBOUND.
CHART FAS OBST: 812 TOWER (GU-020003) 132922N/1444946E.
CHART VDP AT 2.43 NM TO RW24R.
PAVYI TO RW24R: 3.00/75.
CHART CIRCLING ICON.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ CAT A, B 900-2, CAT C, D 900-2 1/2

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	1160	1	855	1160	1 1/4	855	1160	2 1/2	855	1160	2 1/2	855			
CIRCLING	1160	1 1/4	855	1160	1 1/4	855	1160	2 1/2	855		NA				

CHANGES - REASONS

1. LOCATION IDENTIFIER: CHANGED LOCATION IDENTIFIER FROM GUAM TO TAMUNING - 28 DAY TRACKER REVIEW #27520

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER: GUAM CERAP, AGANA ATCT, AMGR

FLIGHT CHECKED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

Digitally signed by
RAKE MCGRAW
Jul 01, 2025

OFFICE
DATE

DEVELOPED BY
JANTZEN TAYLOR

Digitally signed by
JANTZEN L TAYLOR
Feb 04, 2025

OFFICE
AJV-A422
DATE
02/04/2025

APPROVED BY
RAKE MCGRAW

Digitally signed by
RAKE MCGRAW
Jul 01, 2025

OFFICE
AJV-A422
DATE

TITLE
MANAGER

