

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW20 LNAV: RW20 CLIMB TO 2300 DIRECT YUKIS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 023.05 INBOUND. CHART FAS OBST: 1019 BLDG 413638N/0864330W CHART FAS OBST: 946 TWR 413604N/0864257W WAAS CHANNEL # 87034 REFERENCE PATH ID: W20A CHART CIRCLING ICON. BOTIW TO RW20: 3.00/40 LTP HAE: 213.6 M											
NOMES	BOOTE (FO)	339.98 / 15.88	2500												
STYLE	BOOTE (FO)	096.42 / 7.60	2500												
WOXIN (IAF)	BOOTE (NOPT) (FB)	152.55 / 8.37	2500												
GIJ VORTAC (IAF)	BOOTE (NOPT) (FB)	272.56 / 14.42	2500												
BOOTE (IF/IAF)	BOTIW (FB)	203.16 / 6.82	2500												
BOTIW (FAF)	ZAXEP/2.00 NM TO RW20 (FB)	203.13 / 3.18													
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)															
2. HOLD NE BOOTE, RT, 203.16 INBOUND, 2500 FT. IN LIEU OF PT (IAF)															
3. FAC: 203.13 FAF: BOTIW _____ DIST FAF TO MAP: 5.18 THLD: 5.18															
4. MIN. ALT: BOOTE 2500, BOTIW 2500, ZAXEP/2.00 NM TO RW20 1480															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: RW20 3000															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1200	1	388	1200	1	388	1200	1 1/8	388	1200	1 1/8	388			
LNAV MDA	1280	1	468	1280	1	468	1280	1 3/8	468	1280	1 3/8	468			
CIRCLING	1320	1	508	1320	1	508	1560	2 1/4	748	1560	2 1/2	748			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON GIJ VORTAC AIRWAY RADIALS 209 CW 310. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SOUTH BEND ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE LP CAT C/D AND LNAV CAT C/D VISIBILITY 1/8 MILE. (SEE FORM 8260-10)															
CITY AND STATE LA PORTE, IN				ELEVATION: 812 THRE: 812 AIRPORT NAME: LA PORTE MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1 19 SEPTEMBER 2013				SUP: AMDT: ORIG DATED 07/05/2007			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ZAXEP/2.00 NM TO RW20	RW20 (MAP) (FO)	203.13 / 2.00	
RW20 (MAP)	1200 MSL	203.13	
1200 MSL	YUKIS (FO)		2300

NOTES, (CONT.):

CHART NOTE: RWY 20 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.
CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

CITY AND STATE
LA PORTE, IN

ELEVATION: 812 THRE: 812
AIRPORT NAME:
LA PORTE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 20, AMDT 1
19 SEPTEMBER 2013

SUP:
AMDT: ORIG
DATED: 07/05/2007

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KPPO
RUNWAY RW20
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W20A
LTP/FTP LATITUDE 413442.3500N
LTP/FTP LONGITUDE 0864352.9195W
LTP/FTP ELLIPSOIDAL HEIGHT +02136
FPAP LATITUDE 413318.6300N
FPAP LONGITUDE 0864433.7000W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1224
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

634A8394

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +02474
FPAP ORTHOMETRIC HEIGHT +02474

CITY AND STATE LA PORTE, IN	ELEVATION: 812 THRE: 812 AIRPORT NAME: LA PORTE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1 19 SEPTEMBER 2013	SUP:
				AMDT: ORIG
				DATED: 07/05/2007

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KPPOK5FR20	AGIJ	010GIJ	K5D 0V	A	IF				18000		A	JS
SUSAP	KPPOK5FR20	AGIJ	020BOOTEK5EA0EE	B	010TF		27260144	+	02500			A	JS
SUSAP	KPPOK5FR20	ANOMES	010NOMESK5EA0E		IF					18000		A	JS
SUSAP	KPPOK5FR20	ANOMES	020BOOTEK5EA0EY		020TF		34000159	+	02500			A	JS
SUSAP	KPPOK5FR20	ANOMES	030BOOTEK5EA0EE	AR	HF		20320040	+	02500			A	JS
SUSAP	KPPOK5FR20	ASTYLE	010STYLEK5EA0E		IF					18000		A	JS
SUSAP	KPPOK5FR20	ASTYLE	020BOOTEK5EA0EY		020TF		09640076	+	02500			A	JS
SUSAP	KPPOK5FR20	ASTYLE	030BOOTEK5EA0EE	AR	HF		20320040	+	02500			A	JS
SUSAP	KPPOK5FR20	AWOXIN	010WOXINK5EA0E	A	IF					18000		A	JS
SUSAP	KPPOK5FR20	AWOXIN	020BOOTEK5EA0EE	B	010TF		15260084	+	02500			A	JS
SUSAP	KPPOK5FR20	R	010BOOTEK5EA0E	I	IF			+	02500	18000		A	JS
SUSAP	KPPOK5FR20	R	020BOTIWK5EA1E	F	051TF		20320068	+	02500		RW20	K5PGA	JS
SUSAP	KPPOK5FR20	R	020BOTIWK5EA2WALP			N	ALNAV						JS
SUSAP	KPPOK5FR20	R	021ZAXEPK5EA0E	S	031TF		20310032	V	0148001489	-300		A	JS
SUSAP	KPPOK5FR20	R	030RW20	K5PGOGY	M	031TF	20310020		00852	-300		A	JS
SUSAP	KPPOK5FR20	R	040		0	M	2031	+	01200			A	JS
SUSAP	KPPOK5FR20	R	050YUKISK5EA0EY		DF			+	02300			A	JS
SUSAP	KPPOK5FR20	R	060YUKISK5EA0EE	R	HM		02310040	+	02300			A	JS

1 2 3 4 5 6 7 8 9 0 1

SUP:	
AMDT:	ORIG
DATED:	07/05/2007

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

RUNWAY 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KPPOK5GRW20 0050002031 N41344235W086435292-0200 +0213600812000040075R

1 2 3 4 5 6 7 8 9 0 1 2 3
PP 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KPPOK5PR20 RW20 001 0000W20A0N4134423500W08643529195+021360300N4133186300W08644337000106751224000400F400000634A8394

SUSAP KPPOK5PR20 RW20 002E +02474+02474LP 87034

1 2 3 4 5 6 7 8 9 0 1 2 3
MSA 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KPPOK5SRW20 K5PG 0 18018003025

M

QUALITY
CHECKED

CITY AND STATE
LA PORTE, IN

ELEVATION: 812 THRE: 812
AIRPORT NAME:
LA PORTE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 20, AMDT 1
19 SEPTEMBER 2013

SUP:

AMDT: ORIG

DATED: 07/05/2007

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	GIJ	GIJ	010	IAF	IF		FB					
	GIJ	BOOTE	020		TF		FB	1.0	272.6(269.6T)	014.4	AA 02500	
	NOMES	NOMES	010		IF		FB					
	NOMES	BOOTE	020		TF		FO	2.0	340.0(337.0T)	015.9	AA 02500	
	NOMES	BOOTE	030	IAF	HF	R	FO		203.2(200.2T)	004.0	AA 02500	
	STYLE	STYLE	010		IF		FB					
	STYLE	BOOTE	020		TF		FO	2.0	096.4(093.4T)	007.6	AA 02500	
	STYLE	BOOTE	030	IAF	HF	R	FO		203.2(200.2T)	004.0	AA 02500	
	WOXIN	WOXIN	010	IAF	IF		FB					
	WOXIN	BOOTE	020		TF		FB	1.0	152.6(149.6T)	008.4	AA 02500	
		BOOTE	010	FACF	IF		FB				AA 02500	
		BOTIW	020	FAF	TF		FB	0.5	203.2(200.2T)	006.8	AA 02500	
		ZAXEP	021	SDF	TF		FB	0.3	203.1(200.1T)	003.2	AA 01480	GS 01489
		RW20	030	MAP	TF		FO	0.3	203.1(200.1T)	002.0	AT 00852	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		203.1(200.1T)		AA 01200	
	YUKIS	050		DF		FO				AA 02300	
	YUKIS	060		HM	R	FO		023.1(020.1T)	004.0	AA 02300	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	GIJ	N414607.00	W0861906.42	N4146.117	W08619.107
	BOOTE	N414558.69	W0863822.27	N4145.978	W08638.371
	BOTIW	N413934.09	W0864130.55	N4139.568	W08641.509
	NOMES	N413121.81	W0863004.56	N4131.364	W08630.076
	STYLE	N414626.30	W0864830.18	N4146.438	W08648.503
	WOXIN	N415311.81	W0864402.28	N4153.197	W08644.038
	YUKIS	N412341.37	W0864914.16	N4123.690	W08649.236
	ZAXEP	N413635.09	W0864257.94	N4136.585	W08642.966
	RW20	N413442.35	W0864352.92	N4134.706	W08643.882

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW20	00812	40



CITY AND STATE LA PORTE, IN	ELEVATION: 812	THRE: 812	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 20, AMDT 1	AMDT: ORIG
	LA PORTE MUNI	RNAV	19 SEPTEMBER 2013	DATED: 07/05/2007	