

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ZUBUK (IF/IAF)	EGCUP (FB)	182.43 / 8.00	2100	LPV: DA LNAV/VNAV: DA LNAV: RW18
EGCUP (FAF)	JOBIV/1.70 NM TO RW18 (FB)	182.43 / 4.28		
JOBIV/1.70 NM TO RW18	RW18 (MAP) (FO)	182.43 / 1.70		CLIMB TO 2100 DIRECT YECUD AND HOLD.
RW18 (MAP)	471 MSL	182.43		
471 MSL	YECUD (FO)		2100	

ADDITIONAL FLIGHT DATA:
HOLD S, RT, 002.43 INBOUND.
CHART FAS OBST: 257 TREE 333032N/0900519W
CHART: 272 TREE 333155N/0900436W
DISTANCE TO THLD FROM 326 HATH: 0.86 NM.
CHART VDP AT 1.02 MILES TO RW18*
*LNAV ONLY.
WAAS CHANNEL # 50199
REFERENCE PATH ID: W18A
LTP HAE: 17.7 M

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N ZUBUK, RT, 182.43 INBOUND, 2100 FT. IN LIEU OF PT (IAF)
- FAC: 182.43 FAF: EGCUP DIST FAF TO MAP: 5.98 THLD: 5.98
- MIN. ALT: ZUBUK 2100, EGCUP 2100, JOBIV/1.70 NM TO RW18 720*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2100 GS ALT AT: EGCUP 2100 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 50.7 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 1W EPOCH YEAR: 2015

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	471	3/4	326	471	3/4	326	471	3/4	326	471	3/4	326			
LNAV/VNAV DA	566	1	421	566	1	421	566	1	421	566	1	421			
LNAV MDA	520	3/4	375	520	3/4	375	520	3/4	375	520	3/4	375			
CIRCLING	760	1	605	760	1	605	780	1 3/4	625	780	2	625			

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22C (-8F) OR ABOVE 54C @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
(130F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: BARO-VNAV AND VDP NA WHEN USING GREENVILLE ALTIMETER SETTING.
(SEE FORM 8260-10)



CITY AND STATE GREENWOOD, MS	ELEVATION: 155 THRE: 145 AIRPORT NAME: GREENWOOD-LEFLORE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 2	SUP: AMDT: 1 DATED 12/22/2005
---------------------------------	--	------------------------------	---	-------------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALSR, WHEN USING GREENVILLE ALTIMETER SETTING, INCREASE LNAV/VNAV ALL

CATS VISIBILITY 1/8 MILE, LNAV CAT A/B VISIBILITY 1/4 MILE AND LNAV CAT C/D VISIBILITY 3/8 MILE.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREENVILLE ALTIMETER SETTING AND

INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 3/8 MILE, LNAV CAT C/D

VISIBILITY 1/4 MILE AND CIRCLING CAT C/D VISIBILITY 1/2 MILE.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV AND LNAV ALL CATS VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: CIRCLING TO RWY 05/23/27 NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	092/30 CW 272/30 (NOPT)	ZUBUK (IF/IAF) (FB)	2100
3.	272/30 CW 092/30	272/14 CW 092/14	3200
	272/14 CW 092/14	ZUBUK (IF/IAF) (FO)	2100



CITY AND STATE GREENWOOD, MS	ELEVATION: 155 THRE: 145 AIRPORT NAME: GREENWOOD-LEFLORE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 2	SUP:
				AMDT: 1
				DATED: 12/22/2005

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KGWO
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	332956.8705N
LTP/FTP LONGITUDE	0900516.8635W
LTP/FTP ELLIPSOIDAL HEIGHT	+00177
FPAP LATITUDE	332827.6325N
FPAP LONGITUDE	0900519.5225W
THRESHOLD CROSSING HEIGHT (TCH)	00050.7
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 12B531C8

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00442
FPAP ORTHOMETRIC HEIGHT	+00442



CITY AND STATE GREENWOOD, MS	ELEVATION: 155 THRE: 145 AIRPORT NAME: GREENWOOD-LEFLORE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 2	SUP:
				AMDT: 1
				DATED: 12/22/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	ZUBUK	ZUBUK	010	IAF	HF	R	FO		182.4 (181.4T)	004.0	AA 02100	
		ZUBUK	010	FACF	IF		FB				AA 02100	
		EGCUP	020	FAF	TF		FB	0.5	182.4 (181.4T)	008.0	AA 02100	
		JOBIV	021	SDF	TF		FB	0.3	182.4 (181.4T)	004.3	AA 00720	GS 00737
		RW18	030	MAP	TF		FO	0.3	182.4 (181.4T)	001.7	AT 00196	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		182.4 (181.4T)		AA 00471	
	YECUD	050		DF		FO				AA 02100	
	YECUD	060		HM	R	FO		002.4 (001.4T)	004.0	AA 02100	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EGCUP	N333556.21	W0900506.14	N3335.937	W09005.102
	JOBIV	N333139.03	W0900513.82	N3331.651	W09005.230
	YECUD	N331528.94	W0900542.65	N3315.482	W09005.711
	ZUBUK	N334357.08	W0900451.76	N3343.951	W09004.863
	RW18	N332956.87	W0900516.86	N3329.948	W09005.281

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18	00145	51



CITY AND STATE GREENWOOD, MS	ELEVATION: 155 THRE: 145	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 2	SUP:
	AIRPORT NAME: GREENWOOD-LEFLORE			AMDT: 1
				DATED: 12/22/2005