

**Federal Aviation
Administration**

Transmittal Letter 17-17

June 30, 2017

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
17-Aug-17	MS	Greenwood	Greenwood-Leflore	7/0300	6/9/17	RNAV (GPS) RWY 18, Amdt 2A

AIRAC Date: 17 AUGUST 2017

FDC 7/0300 GWO IAP GREENWOOD-LEFLORE, Greenwood, MS. RNAV (GPS) RWY 18, AMDT 2A... CHART TDZE 145, DELETE THRE 145. CHART APT ELEV 162. CHART CIRCLING ICON. CIRCLING CAT A/B HAA 598, CAT C MDA 1000/HAA 838, CAT D MDA 1120/HAA 958, VIS CAT C 2-1/2, CAT D 3. CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: RWY 5, 23, 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: CIRCLING RWY 5, 23, 27 NA AT NIGHT. DELETE NOTE: CIRCLING TO RWY 5/23/27 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREENVILLE ALTIMETER SETTING: INCREASE LPV DA TO 580 FEET AND VISIBILITY 1/4 SM, LNAV/VNAV DA TO 675 FEET AND VISIBILITY 3/8 SM; INCREASE ALL MDAS 120 FEET AND VISIBILITY LNAV CAT C/D 1/4 SM AND CIRCLING CAT C 1/2 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREENVILLE ALTIMETER SETTING AND INCREASE ALL DA 108 FT AND MDA 120 FT AND INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 3/8 MILE, LNAV CAT C/D VISIBILITY 1/4 MILE AND CIRCLING CAT C/D VISIBILITY 1/2 MILE. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, AND LNAV ALL CATS TO 1 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE. CHART NOTE: FOR INOPERATIVE ALS WHEN USING GREENVILLE ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 1/2 SM, AND LNAV/VNAV ALL CATS TO 1 3/4 SM, AND LNAV CAT A/B TO 1 SM, AND CAT C/D TO 1 3/8 SM. DELETE NOTE: FOR INOPERATIVE MALSR, WHEN USING GREENVILLE

ALTIMETER SETTING, INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE, LNAV CAT A/B VISIBILITY 1/4 MILE AND LNAV CAT C/D VISIBILITY 3/8 MILE. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 900-2 1/2, CAT D 1000-3, AND NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 18, AMDT 2B. 1705041504-PERM