

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 NDB STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LIMPS INT	FULER LOM	005.50 / 14.60	2700

MAP: 5.37 MILES AFTER FULER LOM
 CLIMB TO 3100 THEN LEFT TURN DIRECT OS LOM AND HOLD.

ADDITIONAL FLIGHT DATA:
 HOLD W, LT, 092.07 INBOUND.
 FAS OBST: 1159 AAO 400402N/0831016W
 OS LOM TO RW09R: 3.07/51.

1. PT R SIDE OF COURSE 272.71 OUTBOUND 2700 FT WITHIN 10 MILES OF FULER LOM (IAF)
- 2.
3. FAC 092.71 FAF FULER LOM DIST FAF TO MAP 5.37 THLD 5.37
4. MIN. ALT FULER LOM 2700
8. MSA FROM: OS LOM 3100

MAG VAR: 5W EPOCH YEAR:1990

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY >>>>>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-9R	1460	3/4	559	1460	3/4	559	1460	1 1/8	559	1460	1 1/8	559			
CIRCLING	1460	1	555	1460	1	555	1460	1 5/8	555	1460	2	555			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PORT COLUMBUS ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET. INCREASE S-9R CAT C/D AND CIRCLING CAT C VISIBILITY 1/8 MILE.

@ NA WHEN CONTROL TOWER CLOSED.
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE COLUMBUS, OH	ELEVATION: 905	THRE: 901	FACILITY IDENTIFIER: OSU	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 9R, AMDT 3 10 MAR 2011	SUP
	AIRPORT NAME: OHIO STATE UNIVERSITY				AMDT 2B
					DATE 08/15/2000