

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	IA	Mason City	Mason City Muni	1/5287	4/27/2021	RNAV (GPS) RWY 18, Amdt 2B

Airac Date: 15 JULY 2021

FDC 1/5287 MCW IAP MASON CITY MUNI, MASON CITY, IA. RNAV (GPS) RWY 18, AMDT 2B... CIRCLING CAT A MDA 1680/HAA 467, CAT B MDA 1760/HAA 547, CAT C MDA 1780/HAA 567. DELETE PBN REQUIREMENTS NOTE: RNP APCH. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLES CITY ALTIMETER SETTING AND INCREASE ALL DA 87 FEET; INCREASE ALL MDA 100 FEET AND LNAV CAT C/D AND CIRCLING CAT C VISIBILITY 1/4 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLES CITY ALTIMETER SETTING AND INCREASE LPV DA TO 1500 FEET, LNAV/VNAV DA TO 1550; INCREASE ALL MDA 100 FEET AND LNAV CATS C AND D VISIBILITY 1/4 SM AND CIRCLING CAT C 1/4 SM. DELETE NOTE: FOR INOP MALS WHEN USING CHARLES CITY ALTIMETER SETTING, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/8 SM; LNAV CATS C/D VISIBILITY TO 1 3/8 SM. CHART NOTE: FOR INOPERATIVE ALS WHEN USING CHARLES CITY ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 7/8 SM; LNAV CATS C/D VISIBILITY TO 1 3/8 SM. THIS IS RNAV (GPS) RWY 18, AMDT 2C.
2104252131-PERM