

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 5, STANDARD WITH MINIMUM CLIMB OF 354 FEET PER NM TO 2500 OR 1000-2 1/2 FOR CLIMB IN VISUAL CONDITIONS.
RWY 23, STANDARD

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 5: FOR CLIMB IN VISUAL CONDITIONS CROSS MOORE-MURRELL AIRPORT AT OR ABOVE 2200 THEN VIA VXV VORTAC R-060 INBOUND TO 4000 BEFORE PROCEEDING ON COURSE.

RWY 23: CLIMB HEADING 233.43 AND VXV VORTAC R-060 INBOUND TO 4000 BEFORE PROCEEDING ON COURSE.

This is a corrected copy of a procedure published in TL 10-13, on 14 May 2010.

** Amendment Number corrected FROM 3 TO 6. **

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 05: POLE 2187' FROM DER, 517' RIGHT OF CENTERLINE, UP TO 16' AGL/1356' MSL. VEHICLE ON ROAD 2019' FROM DER, 1018' LEFT OF CENTERLINE, UP TO 17' AGL/1337' MSL. WINDSOCK 66' FROM DER, 189' LEFT OF CENTERLINE, UP TO 8' AGL/1282' MSL. RAILROAD AT DER, 295' RIGHT OF CENTERLINE, UP TO 15' AGL/1288' MSL. TREES BEGINNING 1065' FROM DER, 464' LEFT OF CENTERLINE, UP TO 54' AGL/1414' MSL. TREES BEGINNING 191' FROM DER, 274' RIGHT OF CENTERLINE, UP TO 51' AGL/1311' MSL.

NOTE: RWY 23, POLE 1442' FROM DER, 451' RIGHT OF CENTERLINE, UP TO 54' AGL/1367' MSL. VEHICLE ON ROAD 23' FROM DER, 337' LEFT OF CENTERLINE, UP TO 17' AGL/1367' MSL. VEHICLE ON ROAD 1246' FROM DER, 113' RIGHT OF CENTERLINE, UP TO 17' AGL/1369' MSL. (CONT'D)

(4) CONTROLLING OBSTACLES:

RWY 23: 6821 MSL AAO 354218.00N/0831527.00W

RWY 05: 2116 MSL TOWER 361342.34N/0831955.62W, 2139 MSL AAO 361348.03N/0831948.22W

RWY 05 (VCOA): 1855 MSL TREE 361257.40N/0832055.17W

(5) City, State

MORRISTOWN, TN

(6) Airport

MOORE-MURRELL

(7) Effective Date

29 JUL 2010

(8) Amdt. No.

6

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
DEPARTURE PROCEDURE (CONTINUATION) FAA FORM 8260-15A
FLIGHT STANDARDS SERVICE**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

(3) TAKEOFF OBSTACLE NOTE: (CONT'D)

TREES BEGINNING 1774' FROM DER, 753' RIGHT OF CENTERLINE, UP TO 100' AGL/1460' MSL. BUILDINGS 1583' FROM DER, 690' RIGHT OF CENTERLINE, UP TO 30' AGL/1370' MSL.

City, State MORRISTOWN, TN		Airport MOORE-MURRELL			Effective Date 29 JUL 2010	Amdt. No. 6
DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date	