

**Federal Aviation  
Administration**

**Transmittal Letter 22-11**

**APRIL 1, 2022**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/19/2022	IL	Lawrenceville	Lawrenceville -Vincennes Intl	2/8098	3/24/2022	RNAV (GPS) RWY 18, Amdt 1B

**AIRAC Date: 19 MAY 2022**

FDC 2/8098 LWV IAP LAWRENCEVILLE-VINCENNES INTL, LAWRENCEVILLE, IL. RNAV (GPS) RWY 18, AMDT 1B... CIRCLING CAT D MDA 1160/730 HAA. CIRCLING CAT D VISIBILITY 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MOUNT CARMEL ALTIMETER SETTING: INCREASE LPV DA TO 656 FEET; INCREASE LNAV/VNAV DA TO 902 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C/D 1/4 SM, AND CIRCLING VISIBILITY CAT D 1/4 SM. ALTERNATE MINIMUMS: CAT D 800-2 1/4; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 18, AMDT 1C. 2203231233-PERM