

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
BINNS	UNYTS (FO)	264.88 / 5.70	3000	LPV: DA LNAV/VNAV: DA LNAV: RW16
HYPER	UNYTS (FO)	055.69 / 6.30	3000	CLIMB TO 2200 DIRECT NABIC THEN CLIMBING LEFT TURN TO 3000 ON TRACK 070.00 TO FIGID AND HOLD.
UNYTS (IF/IAF)	NISPL (FB)	158.94 / 6.86	1900	
NISPL (FAF)	RW16 (MAP) (FO)	159.00 / 3.35		
RW16 (MAP)	2200 MSL	159.00	2200	ADDITIONAL FLIGHT DATA: HOLD E, RT, 250.08 INBOUND. CHART FAS OBST: 1019 TREE 393628N/0770113W DISTANCE TO THLD FROM 292 HATH: 0.77 NM. WAAS CHANNEL # 65607 REFERENCE PATH ID: W16A LTP HAF: 208 2 M
2200 MSL	NABIC (FB)		2200	
NABIC	FIGID (FO)	070.00 / 6.50	3000	

8. MSA FROM: RW16 3400

MAG VAR: 11W

EPOCH YEAR: 2000

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N/A

STANDARD

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1081	1	292	1081	1	292	1081	1	292		NA				
LNAV/VNAV DA	1189	1 3/8	400	1189	1 3/8	400	1189	1 3/8	400		NA				
LNAV MDA	1280	1	491	1280	1	491	1280	1 3/8	491		NA				

CIRCLING

[illegible]

NOTES:

CHART NOTE: BARO-VNAV NA WHEN USING FREDERICK ALTIMETER SETTING.

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FREDERICK ALTIMETER SETTING AND

INCREASE ALL DA 116 FEET AND ALL MDA 120 FEET; INCREASE LPV ALL CATS AND LNAV CAT C VISIBILITY

(SEE FORM 8260-10)

CITY AND STATE

ELEVATION: 789

THRE: 789

AIRPORT NAME:

**CARROLL COUNTY RGNL/JACK B POAGE
FIELD**

FACILITY

IDENTIFIER:
RNAV

PROCEDURE NO. /AMDT NO. /EFFECTIVE DATE:

RNAV (GPS) RWY 16, AMDT 2

31 MAY 2012

SUP: C	
--------	--

AMDT:

DATED 08/30/2007

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

3/8 MILE, AND LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 16 PROCEDURE NA AT NIGHT.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BINNS ON V265 NORTHBOUND.

QUALITY
1
CHECKED

CITY AND STATE

WESTMINSTER, MD

ELEVATION: 789

THRE: 789

AIRPORT NAME:

CARROLL COUNTY RGNL/JACK B POAGE
FIELDFACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 16, AMDT 2

31 MAY 2012

SUP:

AMDT: 1

DATED: 08/30/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KDMW
RUNWAY RW16
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W16A
LTP/FTP LATITUDE 393651.1750N
LTP/FTP LONGITUDE 0770044.8215W
LTP/FTP ELLIPSOIDAL HEIGHT +02082
FPAP LATITUDE 393535.5300N
FPAP LONGITUDE 0765943.7700W
THRESHOLD CROSSING HEIGHT (TCH) 00045.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1192
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

0F593470

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +02405
FPAP ORTHOMETRIC HEIGHT +02405

 QUALITY
2
CHECKED

CITY AND STATE WESTMINSTER, MD	ELEVATION: 789 AIRPORT NAME: CARROLL COUNTY RGNL/JACK B POAGE FIELD	THRE: 789	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 2 31 MAY 2012	SUP:
					AMDT: 1
					DATED: 08/30/2007

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KDMWK6FR16	ABINNS 010BINNSK6EA0E	IF							18000			A JS	
SUSAP KDMWK6FR16	ABINNS 020UNYTSK6EA0EY	020TF			26490057		+ 03000					A JS	
SUSAP KDMWK6FR16	ABINNS 030UNYTSK6EA0EE	AR HF			15900040		+ 03000					A JS	
SUSAP KDMWK6FR16	AHYPER 010HYPERK6EA0E	IF						18000				A JS	
SUSAP KDMWK6FR16	AHYPER 020UNYTSK6EA0EY	020TF			05570063		+ 03000					A JS	
SUSAP KDMWK6FR16	AHYPER 030UNYTSK6EA0EE	AR HF			15900040		+ 03000					A JS	
SUSAP KDMWK6FR16	R 010UNYTSK6EA0E	I IF					+ 03000	18000				A JS	
SUSAP KDMWK6FR16	R 020NISPLK6EA1E	F 051TF			15890069		+ 01900				RW16	K6PGA JS	
SUSAP KDMWK6FR16	R 020NISPLK6EA2WALPV		ALNAV/VNAV	ALNAV								JS	
SUSAP KDMWK6FR16	R 030RW16	K6PGOGY M 031TF			15900034		00834		-300			A JS	
SUSAP KDMWK6FR16	R 040	0 M CA			1590		+ 02200					A JS	
SUSAP KDMWK6FR16	R 050NABICK6EA0E	DF					+ 02200					A JS	
SUSAP KDMWK6FR16	R 060FIGIDK6EA0EY	L010TF			0700		+ 03000					A JS	
SUSAP KDMWK6FR16	R 070FIGIDK6EA0EE	R HM			25010040		+ 03000					A JS	

[illegible]

QUALITY
1
CHECKED

ELEVATION: 789 THRE: 789
AIRPORT NAME:
CARROLL COUNTY RGNL/JACK B POAGE
FIELD

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, AMDT 2
31 MAY 2012

SUP:	
AMDT:	1
DATED:	08/30/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

	1	2	3	4	5	6	7	8	9	0	1	2	3		
MSA	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890	12345678901234567890		

SUSAP KDMWK6SRW16 K6PG					0	18018003425									M

QUALITY
CHECKED

CITY AND STATE WESTMINSTER, MD	ELEVATION: 789 THRE: 789 AIRPORT NAME: CARROLL COUNTY RGNL/JACK B POAGE FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 2 31 MAY 2012	SUP:
				AMDT: 1
				DATED: 08/30/2007