

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH					
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LNAV: RW22					
LAWTO (IF/IAF)			EVAJI (TF) (FB) (RNP 1.00)			220.27 / 6.90			2600			CLIMB TO 3000 DIRECT YEDUK AND HOLD.					
EVAJI (FAF)			WOKOP/2.00 NM TO RW22 (TF) (FB) (RNP 0.30)			225.71 / 2.82											
WOKOP/2.00 NM TO RW22			RW22 (MAP) (TF) (FO) (RNP 0.30)			225.71 / 2.00											
RW22 (MAP)			1429 MSL (CA)			225.71			3000								
1429 MSL			YEDUK (DF) (FO) (RNP 1.00)									ADDITIONAL FLIGHT DATA: HOLD SW, RT, 045.57 INBOUND. CHART FAS OBST: 1144 TREE 403628N/0833757W. CHART LIMA ASOS CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. HOLD NE LAWTO, RT, 220.27 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																	
3. FAC: 225.71 FAF: EVAJI DIST FAF TO MAP: 4.82 THLD: 4.82																	
4. MIN. ALT: LAWTO 3000, EVAJI 2600, WOKOP/2.00 NM TO RW22 1680																	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: _____ TCH: 20:1 IS NOT CLEAR 34:1 IS NOT CLEAR																	
8. MSA FROM: RW22 3000																	
MAG VAR: 6W EPOCH YEAR: 2010																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT												ALTERNATE: N A X					
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA	1460	1	438	1460	1	438	1460	1 1/4	438	1460	1 1/2	438					
CIRCLING	1580	1	551	1600	1	571	1600	1 1/2	571	1600	2	571					
NOTES: CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE LIMA ALTIMETER SETTING. PBN REQUIRMENT NOTE: RNP APCH																	
CITY AND STATE KENTON, OH				ELEVATION: 1029 TDZE: 1022 AIRPORT NAME: HARDIN COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG-A 24 MAY 2018				SUP: AMDT: ORIG DATED 01/13/2011			