

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW10 CLIMB TO 5700 DIRECT WIPGU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 283.68 INBOUND. CHART FAS OBST: 2701 TOWER 374646N/0810920W 2800 AAO 374809N/0811355W DISTANCE TO THLD FROM 200 HATH: 0.44 NM. CHART VDP AT 1.30 MILES TO RW10* *LNAV ONLY. WAAS CHANNEL # 82023 REFERENCE PATH ID: W10A LTP HAE: 726.6 M											
BKW VORTAC	OTUCU (FO)	283.97 / 12.15	5300												
BIVDY (IAF)	OTUCU (NOPT) (FB)	117.75 / 13.94	5300												
PINEE (IAF)	OTUCU (NOPT) (FB)	055.18 / 15.03	5300												
OTUCU (IF/IAF)	WEXIV (FB)	103.35 / 6.19	4300												
WEXIV (FAF)	ZUPIK/1.90 NM TO RW10 (FB)	103.43 / 3.61													
ZUPIK/1.90 NM TO RW10	RW10 (MAP) (FO)	103.47 / 1.90													
(SEE FORM 8260-10)															
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD W OTUCU, RT, 103.35 INBOUND, 5300 FT. IN LIEU OF PT (IAF) 3. FAC: <u>103.43</u> FAF: <u>WEXIV</u> DIST FAF TO MAP: <u>5.51</u> THLD: <u>5.51</u> 4. MIN. ALT: OTUCU 5300, WEXIV 4300, ZUPIK/1.90 NM TO RW10 3140* 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>4300</u> GS ALT AT: OTUCU 4300 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>59.0</u> 34:1 IS CLEAR 8. MSA FROM: RW10 5400				MAG VAR: 6W EPOCH YEAR: 1985											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	2686	3/4	200	2686	3/4	200	2686	3/4	200	2686	3/4	200			
LNAV/VNAV DA	3000	1 3/4	514	3000	1 3/4	514	3000	1 3/4	514	3000	1 3/4	514			
LNAV MDA	2960	1	474	2960	1	474	2960	1 3/8	474	2960	1 3/8	474			
CIRCLING	3120	1	616	3180	1	676	3180	2	676	3180	2 1/4	676			
NOTES: CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 28 NA AT NIGHT. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-2F) OR ABOVE 28C (82F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BKW VORTAC ON V258 SOUTHEAST BOUND. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 2504 THRE: 2486		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
BECKLEY, WV		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 10, AMDT 1				AMDT: ORIG					
		RALEIGH COUNTY MEMORIAL				25 AUG 2011				DATED		03/12/2009			

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES, (CONT.):									
FROM	TO	COURSE AND DISTANCE	ALTITUDE						
RW10 (MAP)	2686 MSL	103.47							
2686 MSL	WIPGU (FO)		5700						
NOTES, (CONT.): *LNAV ONLY CHART NOTE: VDP AND BARO-VNAV NA WHEN USING BLUEFIELD ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BLUEFIELD ALTIMETER SETTING AND INCREASE ALL DA 118 FEET AND ALL MDA 120 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 1/2 MILE, LNAV CAT C/D VISIBILITY 3/8 MILE, AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.									
CITY AND STATE BECKLEY, WV		ELEVATION: 2504 THRE: 2486 AIRPORT NAME: RALEIGH COUNTY MEMORIAL	FACILITY IDENTIFIER: RNAV						
		PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, AMDT 1 25 AUG 2011							
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 2px;">SUP:</td> </tr> <tr> <td style="padding: 2px;">AMDT:</td> <td style="padding: 2px;">ORIG</td> </tr> <tr> <td style="padding: 2px;">DATED:</td> <td style="padding: 2px;">03/12/2009</td> </tr> </table>		SUP:		AMDT:	ORIG	DATED:	03/12/2009
SUP:									
AMDT:	ORIG								
DATED:	03/12/2009								



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBKW
RUNWAY	RW10
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W10A
LTP/FTP LATITUDE	374658.5135N
LTP/FTP LONGITUDE	0810757.4225W
LTP/FTP ELLIPSOIDAL HEIGHT	+07266
FPAP LATITUDE	374646.8500N
FPAP LONGITUDE	0810605.9900W
THRESHOLD CROSSING HEIGHT (TCH)	00059.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

69A3CBAD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+07576
FPAP ORTHOMETRIC HEIGHT	+07576

QUALITY
CHECKED

CITY AND STATE

BECKLEY, WV

ELEVATION: 2504

THRE: 2486

AIRPORT NAME:

RALEIGH COUNTY MEMORIAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 10, AMDT 1

25 AUG 2011

SUP:

AMDT: ORIG

DATED: 03/12/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

[illegible]

QUALITY
4
CHECKED

CITY AND STATE BECKLEY, WV	ELEVATION: 2504 THRE: 2486 AIRPORT NAME: RALEIGH COUNTY MEMORIAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, AMDT 1 25 AUG 2011	SUP:	
				AMDT:	ORIG
				DATED:	03/12/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KBKWK6GRW10 0050011035 N37465851W081075742+0300 +0726602486000059100R

SUSAP KBKWK6PR10	RW10	001	0000W10A0N3746585135W08107574225+072660300N3746468500W08106059900106751224000590F40035069A3CBAD
SUSAP KBKWK6PR10	RW10	002E	+07576+07576LPV 82023

SUSAP KBKWK6SRW10 K6PG 0 18018005425 M

QUALITY
4
CHECKED

ELEVATION: 2504 THRE: 2486
AIRPORT NAME:
RALEIGH COUNTY MEMORIAL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 10, AMDT 1

25 AUG 2011

SUP:	
AMDT:	ORIG
DATED:	03/12/2009