U.S. DEPARTMENT of TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION	TAKEUFF MINIMUMS AND OBSTACLE DEPAR	TURE PROCEDURES (ODP)
Bearings, headings, courses, tracks, and radials are magnetic. Elevational miles. Visibilities are in statute miles or feet RVB unless other	ons and altitudes are in feet, MSL. Affitudes are minimum affitudes unless otherwise indicated.	Ceilings are in feet above airport elevation. Distances are in
(1) TAKEOFF MINIMUMS: RWY 13, 31 STANDARD.		
(2) TEXTUAL DEPARTURE PROCEDURE:		
RIGHT OF CENTERLINE, UP TO 40' AGL/1421 MSL. VEHICLE ON ROAD 38' FROM DER, 285 AGL/1407' MSL. TERRAIN BEGINNING 120' FF	OM DER, 356' RIGHT OF CENTERLINE, 15' AGL/1396' MSL. TRE MSL. NOTE: RWY 31, TERRAIN BEGINNING 32' FROM DER, 2 ' RIGHT OF CENTERLINE, 15' AGL/1418' MSL. FENCE 71' FRO ROM DER, 125' LEFT OF CENTERLINE, UP TO 1447' MSL. FEN BINNING 365' FROM DER, 10' LEFT OF CENTERLINE, UP TO 40 ISL.	20' RIGHT OF CENTERLINE, UP TO 1424' IM DER, 292' LEFT OF CENTERLINE, 4' ICE 198' FROM DER, 299' RIGHT OF
(4) CONTROLLING OBSTACLES:		
		SALITA CO
		OHEO!
(5) City, State VALLEY CITY, ND	(6) Airport BARNES COUNTY MUNI	(7) Effective Date (8) Amdt. No. ORIG