U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 22-19

July 22, 2022

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVEUPONPUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/8/2022	KY	Hopkinsvill e	Hopkinsville- Christian County	2/8135	6/2/2022	RNAV (GPS) RWY 26, Amdt 2

AIRAC Date: 9 SEPTEMBER 2022

FDC 2/8135 HVC IAP HOPKINSVILLE-CHRISTIAN COUNTY, HOPKINSVILLE, KY. RNAV (GPS) RWY 26, AMDT 2... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. CHANGE BARO-VNAV SYSTEMS NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLARKSVILLE ALTIMETER SETTING AND INCREASE LPV DA TO 851 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1033 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 40 FEET AND CIRCLING VISIBILITY CAT C 1/4 SM. LPV VIS ALL CATS 3/4. LNAV/VNAV VIS ALL CATS 1 1/4. DELETE NOTE: NIGHT LANDING: RWY 8 NA. CHART NOTE: CIRCLING RWY 8 NA AT NIGHT. THIS IS RNAV (GPS) RWY 26, AMDT 2A. 2205231327-PERM