

**Federal Aviation
Administration**

Transmittal Letter 20-10

March 20, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	MA	Vineyard Haven	Martha's Vineyard	0/4638	3/10/2020	ILS OR LOC RWY 24, Amdt 3B

AIRAC Date: 23 APRIL 2020

FDC 0/4638 MVY IAP MARTHA'S VINEYARD, VINEYARD HAVEN, MA. ILS OR LOC RWY 24, AMDT 3B... CHART CIRCLING ICON. CIRCLING CAT B MDA 540/HAA 473, CAT C MDA 700/HAA 633, CAT D MDA 780/HAA 713. VIS CAT C 1 3/4 SM, CAT D 2 1/4 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HYANNIS ALTIMETER SETTING AND INCREASE ALL DA TO 317 FEET AND ALL MDA 60 FEET; INCREASE S-LOC CATS C AND D VISIBILITY TO RVR 5000, CIRCLING CAT C AND D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HYANNIS ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET; INCREASE S-LOC CATS C AND D VISIBILITY TO RVR 5000. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4. THIS IS ILS OR LOC RWY 24, AMDT 3C. 2003091930-PERM