

**Federal Aviation
Administration**

Transmittal Letter 24-19

July 19, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/5/2024	SD	Sturgis	Sturgis Muni	4/0079	45441	RNAV (GPS) RWY 29, Amdt 1C

AIRAC Date: 5 SEPTEMBER 2024

FDC 4/0079 49B IAP STURGIS MUNI, STURGIS, SD. RNAV (GPS) RWY 29, AMDT 1C... CHANGE PBN
REQUIREMENTS NOTE TO READ: RNP APCH - GPS. DELETE NOTE: USE ELLSWORTH AFB ALTIMETER
SETTING, WHEN NOT RECEIVED, USE SPEARFISH ALTIMETER SETTING AND INCREASE ALL DA 87 FEET
AND ALL MDA 100 FEET AND INCREASE LPV CAT A/B VISIBILITY 1/4 MILE, AND LPV (WITH CLIMB
GRADIENT) CAT C VISIBILITY 1/2 MILE. CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED
BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -21C OR ABOVE 54C. ALTERNATE MINIMUMS: STANDARD
EXCEPT CAT C 1100-3. THIS IS RNAV (GPS) RWY 29, AMDT 1D. 2405291131-PERM