

**Federal Aviation
Administration**

Transmittal Letter 22-16

June 10, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/14/2022	AL	Tuscaloosa	Tuscaloosa Ntl	2/9905	5/27/2022	RNAV (GPS) RWY 30, Orig-C

AIRAC Date: 14 July 2022

FDC 2/9905 TCL IAP TUSCALOOSA NTL, TUSCALOOSA, AL. RNAV (GPS) RWY 30, ORIG-C... CIRCLING CATS C/D MDA 960/HAA 790, VIS CAT C 2 1/4, CAT D 2 1/2. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 800-2 1/4, CAT D 800-2 1/2; NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: NIGHT LANDING RWY 12, 30 NA AT NIGHT. CHART NOTE: CIRCLING RWY 12, 30 NA AT NIGHT. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BIRMINGHAM ALTIMETER SETTING: INCREASE ALL MDAS 180 FEET AND VISIBILITY LNAV CATS A AND B 1/4 SM, CAT C AND D 1/2 SM, AND CIRCLING CAT C 3/4 SM, CAT D 1/2 SM. THIS IS RNAV (GPS) RWY 30, ORIG-D. 2205251550-PERM