

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> Y51	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> VIROQUA	<u>STATE</u> WI		
<u>AIRPORT ELEVATION</u> 1292	<u>TDZE</u> 1284	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 0E	<u>EPOCH YEAR</u> 2000
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 27 JANUARY 2022	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
FALAR		WIDAL		TF	FB	1.00	087.58	13.84	3000
BOOTY		PENPE		TF	FB	1.00	236.28	7.58	3000
WIDAL	IAF	TEBBO	NOPT	TF	FB	1.00	024.23	5.00	3000
PENPE	IAF	TEBBO	NOPT	TF	FB	1.00	204.29	5.00	3000
TEBBO	IF/IAF	CHIPY		TF	FB	1.00	114.26	5.79	3000
CHIPY	FAF	OPTOE/2.06 NM TO RW11		TF	FB	0.30	114.36	3.27	
OPTOE/2.06 NM TO RW11		RW11	MAP	TF	FO	0.30	114.36	2.06	
RW11	MAP	1620 MSL		CA			114.36		
1620 MSL		TACON		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW11

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT TACON AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF

(IAF)

2. HOLD NW TEBBO, RT, 114.26 INBOUND, 3000 FT. IN LIEU OF PT (IF/IAF), MAX 14000.

3. FAC:

114.36

FAF: CHIPY

DIST FAF TO MAP: 5.33

DIST FAF TO THLD: 5.33

4. MIN ALT: TEBBO 3000, CHIPY 3000, OPTOE/2.06 NM TO RW11 1960

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1: IS CLEAR

20:1: IS CLEAR

TCH:

8. MSA FROM: RW11 3200

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 2 AND 20.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FALAR ON T251 SOUTHBOUND.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BOOTY ON V82-170-510 SOUTHEAST BOUND.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON.
CHIPY TO RW11 3.00/40.
CHART VDP AT 1.01 NM TO RW11.
HOLD SE, RT, 294.60 INBOUND.
CHART FAS OBST: 1358 TREE 433609N/0905706W.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ NA WHEN LOCAL WEATHER NOT AVAILABLE.; STANDARD

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	1620	1	336	1620	1	336		NA			NA				
CIRCLING	1900	1	608	1960	1	668		NA			NA				

CHANGES - REASONS



AIRPORT ID
Y51

PROCEDURE NAME
RNAV (GPS) RWY 11

ORIGINAL/AMENDMENT
ORIG

CITY
VIROQUA

STATE
WI

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZMP, AMGR

FLIGHT CHECKED BY

SCOTT WIEBE

Digitally signed by
DONALD H LANIER
Sep 27, 2021

OFFICE

FPO

DATE

09/23/2021

DEVELOPED BY

DONALD H. LANIER (PETER GETZ)

Digitally signed by
DONALD H LANIER

OFFICE

AJV-A431

DATE

07/23/2020

APPROVED BY

LONNIE EVERHART

Sep 27, 2021
Digitally signed by
DONALD H LANIER
Sep 27, 2021

OFFICE

AJV-A430

DATE

TITLE
MANAGER