

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> GUM/PGUM	<u>PROCEDURE NAME</u> RNAV (GPS) Y RWY 6R	<u>ORIGINAL/AMENDMENT</u> 1E	<u>CITY</u> TAMUNING	<u>STATE</u> GU
<u>AIRPORT ELEVATION</u> 305	<u>TDZE</u> 258	<u>SUPERSEDED</u> RNAV (GPS) Y RWY 6R	<u>DATED</u> 01/25/2024	<u>MAG VAR</u> 2E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ORIGINAL/AMENDMENT</u> 1D	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>EPOCH YEAR</u> 2000
		<u>ACTUAL EFFECTIVE DATE</u> 2 OCTOBER 2025	<u>CANCEL/SUSPEND</u>	

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
UNZ VORTAC		DALPE		TF	FO	1.00	242.61	9.00	3000
ASADE		BURLE		TF	FB	1.00	337.09	28.58	3000
WUVEN		RASPE		TF	FB	1.00	166.30	35.91	3000
BURLE	IAF	DALPE	NOPT	TF	FB	1.00	332.98	9.88	3000
RASPE	IAF	DALPE	NOPT	TF	FB	1.00	152.95	5.12	3000
PULEE	IAF	DALPE	NOPT	TF	FB	1.00	102.10	32.66	3000
DALPE	IF/IAF	FISON		TF	FB	1.00	062.91	7.00	2000
FISON	FAF	HUKES/3.50 NM TO RW06R		TF	FB	0.30	062.93	1.80	
HUKES/3.50 NM TO RW06R		RW06R	MAP	TF	FO	0.30	062.93	3.50	
RW06R	MAP	705 MSL		CA			062.93		
705 MSL		CIBOL		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW06R

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT CIBOL AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1.	PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)									
2.	HOLD SW DALPE, RT, 062.91 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.														
3.	FAC:	062.93	FAF:	FISON	DIST FAF TO MAP:	5.30	DIST FAF TO THLD:	5.30							
4.	MIN ALT:	DALPE 3000, FISON 2000, HUKES/3.50 NM TO RW06R 1440													
5.	DIST TO THLD FROM OM:		MM:		IM:		150 HAT:		GS ANT:						
6.	MIN GP INCPT:		GP ALT AT FAF:						OM:		MM:		IM:		
7.	GP ANGLE:		34:1:	IS NOT CLEAR	20:1:	IS CLEAR	TCH:								
8.	MSA FROM:	RW06R 2600													

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: RWY 6R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ASADE ON B586 SOUTHEAST BOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WUVEN ON A597 NORTHWEST BOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT PULEE ON G467 WESTBOUND.
CHART NOTE: FOR INOPERATIVE ALS, INCREASE CAT A AND B VISIBILITY TO 1 SM, AND CAT C AND D TO 2 SM.
CHART NOTE: CIRCLING NA SE OF RWY 6R-24L.

ADDITIONAL FLIGHT DATA:

HOLD NE, RT, 242.99 INBOUND.
CHART FAS OBST: 724 TOWER (GU-000047) 132746N/1444350E.
CHART VDP AT 2.10 NM TO RW06R.
HUKES TO RW06R: 3.11/55.
CHART CIRCLING ICON.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	980	3/4	722	980	3/4	722	980	1 5/8	722	980	1 5/8	722			
CIRCLING	980	1	675	980	1	675	980	2	675		NA				

CHANGES - REASONS

1. LOCATION IDENTIFIER: CHANGED LOCATION IDENTIFIER FROM GUAM TO TAMUNING - 28 DAY TRACKER REVIEW #27520



COORDINATED WITH:

A4A

X

ALPA

X

AOPA

X

APA

X

HAI

NBAA

X

OTHER:

GUAM CERAP, AGANA ATCT, AMGR

FLIGHT CHECKED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

Digitally signed by

RAKE MCGRAW

Jul 01, 2025

OFFICE

DATE

DEVELOPED BY

JANTZEN TAYLOR

Digitally signed by

JANTZEN L TAYLOR

Feb 03, 2025

OFFICE

AJV-A422

DATE

02/03/2025

APPROVED BY

RAKE MCGRAW

Digitally signed by

RAKE MCGRAW

Jul 01, 2025

OFFICE

AJV-A422

DATE

TITLE

MANAGER

