





US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RAYYY (FAF)	RW10C (MAP) (FO)	092.79 / 4.95	
RW10C (MAP)	869 MSL	092.79	
869 MSL	AGZED (FB)		
AGZED	CGT VORTAC (FO)	160.84 / 29.50	4000

NOTES, (CONT.):

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-2F) OR ABOVE 54C (130F).

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).



CITY AND STATE CHICAGO, IL	ELEVATION: 680	TDZE: 669	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) PRM RWY 10C, ORIG (CLOSE PARALLEL)	SUP:
	AIRPORT NAME: CHICAGO O'HARE INTL				AMDT: NONE
					DATED: