

**Federal Aviation
Administration**

Transmittal Letter 22-23

September 16, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/3/2022	MN	Minneapolis	Anoka County-Blaine (Janes Fld)	2/2223	8/3/2022	RNAV (GPS) RWY 9, Amdt 1

AIRAC Date: 3 NOVEMBER 2022

FDC 2/2223 ANE IAP ANOKA COUNTY-BLAINE (JANES FLD), MINNEAPOLIS, MN. RNAV (GPS) RWY 9, AMDT 1... LPV ALL CATS VIS 7/8. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CRYSTAL ALTIMETER SETTING: INCREASE LPV DA TO 1246 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1373 FEET; INCREASE ALL MDA 40 FEET AND LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT D VISIBILITY 1/4 SM. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING CRYSTAL ALTIMETER SETTING. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16 C OR ABOVE 54 C. THIS IS RNAV (GPS) RWY 9, AMDT 1A. 2208021216-PERM