

**Federal Aviation
Administration**

Transmittal Letter 16-13

May 6, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
23-Jun-16	MS	Hattiesburg	Hattiesburg Bobby L Chain Muni	6/4766	04/18/16	RNAV (GPS) Y RWY 13, Amdt 2A

AIRAC Date: 23 JUNE 2016

FDC 6/4766 HBG IAP HATTIESBURG BOBBY L CHAIN MUNI, HATTIESBURG, MS. RNAV (GPS) Y RWY 13, AMDT 2A... CHANGE THRE 149 TO TDZE 151. CIRCLING CATS B/C MDA 700/HAA 549.. LPV DA 442. LNAV/VNAV DA 523. LNAV HAT 429 ALL CATS. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE 3.00/TCH 50). CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HATTIESBURG-LAUREL RGNL ALTIMETER SETTING AND INCREASE ALL DA 51 FEET AND ALL MDA 60 FEET. INCREASE LPV ALL CATS AND LNAV CAT C/D VISIBILITY 1/8 MILE AND LNAV/VNAV ALL CATS AND CIRCLING CAT C VISIBILITY 1/4 MILE.. THIS IS RNAV (GPS) Y RWY 13, AMDT 2B. 1602161925-PERM