

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
MYCAR	FIVE	MYCAR5.MYCAR	FOUR	03/26/2020	27 Nov 2025

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

This is a corrected copy of the procedure originally published in NFDD 172.
** see page 3 for details. **

DP ROUTE DESCRIPTION:

BURKE LAKEFRONT (KBKL)

TAKEOFF RWY 6L: CLIMB ON HEADING 064.91 TO 1100, THEN ON HEADING 350.00 OR AS ASSIGNED BY ATC, MAINTAIN 2000 (DO NOT CLIMB ABOVE 2000) FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 6R: CLIMB ON HEADING 064.92 TO 1100, THEN ON HEADING 350.00 OR AS ASSIGNED BY ATC, MAINTAIN 2000 (DO NOT CLIMB ABOVE 2000) FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 24L: CLIMB ON HEADING 244.93 TO 1100, THEN RIGHT TURN ON HEADING 350.00 OR AS ASSIGNED BY ATC, MAINTAIN 2000 (DO NOT CLIMB ABOVE 2000) FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY24R: CLIMB ON HEADING 244.92 TO 1100, THEN RIGHT TURN ON HEADING 350.00 OR AS ASSIGNED BY ATC, MAINTAIN 2000 (DO NOT CLIMB ABOVE 2000) FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

CUYAHOGA COUNTY (KCGF)

TAKEOFF RWY 6: CLIMB ON HEADING 057.48 TO 1900, THEN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 24: CLIMB ON HEADING 237.49 TO 1900, THEN RIGHT TURN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

LORAIN COUNTY RGNL (KLPR)

TAKEOFF RWY 7: CLIMB ON HEADING 073.01 TO 1300, THEN ON HEADING 001.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 25: CLIMB ON HEADING 253.02 TO 1300, THEN RIGHT TURN ON HEADING 001.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

LAKE COUNTY EXEC (KLNN)

TAKEOFF RWY 5: CLIMB ON HEADING 052.59 TO 1140, THEN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 10: CLIMB ON HEADING 098.51 TO 1140, THEN LEFT TURN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 23: CLIMB ON HEADING 232.60 TO 1140, THEN RIGHT TURN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

TAKEOFF RWY 28: CLIMB ON HEADING 278.52 TO 1140, THEN ON HEADING 331.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS OCIFR AT OR ABOVE 3000, THENCE...

...ON TRACK 078.64 TO CROSS WHARS AT OR BELOW 14000, THEN ON TRACK 079.07 TO MYCAR. MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE TEN MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS.

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

PROCEDURAL DATA NOTES:

BURKE LAKEFRONT (KBKL)

NOTE: RWY 6R/24L: TAKEOFF MINIMUMS NA WHEN CONTROL TOWER CLOSED.



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
MYCAR	FIVE	MYCAR5.MYCAR	FOUR	03/26/2020	27 Nov 2025

TAKEOFF MINIMUMS:

BURKE LAKEFRONT (KBKL)

RWY 6L, 24R: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1100.

RWY 6R: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1100. NA WHEN CONTROL TOWER CLOSED.

RWY 24L: 400-1 3/8 OR STANDARD WITH MINIMUM CLIMB OF 757 FT/NM TO 1000. NA WHEN CONTROL TOWER CLOSED.

CUYAHOGA COUNTY (KCGF)

RWY 6, 24: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1400.

LORAIN COUNTY RGNL (KLPR)

RWY 7, 25: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1300.

LAKE COUNTY EXEC (KLNN)

RWY 5, 10, 23, 28: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1140.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

BURKE LAKEFRONT (KBKL)

RWY 24L: 740 FT MSL BUILDING 413031.10N/0814144.07W (CLIMB GRADIENT), 896 FT MSL BUILDING 413004.41N/0814214.10W (CEILING/CLIMB GRADIENT TERMINATION ALTITUDE), 787 FT MSL BRIDGE 412953.73N/0814231.66W (VISIBILITY).

MSA:

ALL AIRPORTS: 3100

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

ALL AIRPORTS - CHART: TOP ALTITUDE: ASSIGNED BY ATC.

CHART: MINIMUM CROSSING ALTITUDE AT OCIFR - 3000.

AIRPORT MV: BKL (P) 7W/1990, CGF 8W/1995, LPR 8W/2015, LNN 8W/1995.

DME/DME ASSESSMENT: SAT (RNP 2.0)

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
BKL	CLEVELAND	OH
CGF	CLEVELAND	OH
LPR	LORAIN/ELYRIA	OH
LNN	WILLOUGHBY	OH

COMMUNICATIONS:

BURKE LAKEFRONT (KBKL): CHART: ATIS, BKL ATCT, CLNC DEL, GND CON

CUYAHOGA COUNTY (KCGF): CHART: ATIS, CGF ATCT, CLNC DEL, GND CON

LORAIN COUNTY RGNL (KLPR): CHART: ASOS, CLNC DEL, CTAF

LAKE COUNTY EXEC (KLNN): CHART: AWOS, CTAF

FIXES AND/OR NAVAIDS:



FEDERAL AVIATION ADMINISTRATION
 FLIGHT STANDARDS SERVICE
 DEPARTURE (DATA RECORD)

<u>DP NAME</u>		<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>			
MYCAR		FIVE	MYCAR5.MYCAR	FOUR	03/26/2020	27 Nov 2025			
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
	BURKE LAKEFRONT (KBKL)	-	-	-	-	-			
RW06L (AER)*	413051.82N/0814129.42W*	N	-	-	-	-			*DISPL THLD (178 FT)
1100 MSL	-	-	VA	057.91	-		AT/ABOVE 1100		CG 500 FT PER NM TO 1100
		-	VM	343.00	-		AT 2000		
RW06R (AER)*	413047.12N/0814127.01W*	N	-	-	-	-			*DISPL THLD (275 FT)
1100 MSL	-	-	VA	057.92	-		AT/ABOVE 1100		CG 500 FT PER NM TO 1100
		-	VM	343.00	-		AT 2000		
RW24L (AER)	413112.95N/0814032.20W	N	-	-	-	-			
1100 MSL	-	-	VA	237.93	-		AT/ABOVE 1100		CG 757 FT PER NM TO 1000
		-	VM	343.00	-		AT 2000		RIGHT TURN
RW24R (AER)*	413122.39N/0814024.54W*	N	-	-	-	-			*DISPL THLD (600 FT)
1100 MSL	-	-	VA	237.92	-		AT/ABOVE 1100		CG 500 FT PER NM TO 1100
		-	VM	343.00	-		AT 2000		RIGHT TURN
	CUYAHOGA COUNTY (KCGF)								
RW06 (AER)*	413336.83N/0812938.32W*	N	-	-	-	-			*DISPL THLD (318 FT)
1900 MSL	-	-	VA	049.48	-		AT/ABOVE 1900		CG 500 FT PER NM TO 1400
		-	VM	323.00	-				



DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
MYCAR	FIVE	MYCAR5.MYCAR	FOUR	03/26/2020	27 Nov 2025

FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW24 (AER)*	413406.89N/0812851.49W*	N	-	-	-	-			*DISPL THLD (500 FT)
1900 MSL	-		-	VA	229.49	-	AT/ABOVE 1900		CG 500 FT PER NM TO 1400
			-	VM	323.00	-			RIGHT TURN
	LORAIN COUNTY RGNL (KLPR)		-	-	-	-			
RW07 (AER)	412028.96N/0821109.17W	N	-	-	-	-			
1300 MSL	-		-	VA	065.01	-	AT/ABOVE 1300		CG 500 FT PER NM TO 1300
			-	VM	353.00	-			
RW25 (AER)	412049.83N/0821009.74W	N	-	-	-	-			
1300 MSL	-		-	VA	245.02	-	AT/ABOVE 1300		CG 500 FT PER NM TO 1300
			-	VM	353.00	-			RIGHT TURN
	LAKE COUNTY EXEC (KLNN)		-	-	-	-			
RW05 (AER)*	414052.54N/0812346.84W*	N	-	-	-	-			*DISPL THLD (428 FT)
1140 MSL	-		-	VA	044.59	-	AT/ABOVE 1140		CG 500 FT PER NM TO 1140
			-	VM	323.00	-			
RW10 (AER)	414057.07N/0812346.05W	N	-	-	-	-			
1140 MSL	-		-	VA	090.51	-	AT/ABOVE 1140		CG 500 FT PER NM TO 1140
			-	VM	323.00	-			LEFT TURN



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
MYCAR	FIVE	MYCAR5.MYCAR	FOUR	03/26/2020	27 Nov 2025

<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW23 (AER)	414124.90N/0812304.28W	N	-	-	-	-			
1140 MSL	-	-	-	VA	224.60	-	AT/ABOVE 1140		CG 500 FT PER NM TO 1140
		-	-	VM	323.00	-			RIGHT TURN
RW28 (AER)*	414056.79N/0812304.55W*	N	-	-	-	-			*DISPL THLD (1124 FT)
1140 MSL	-	-	-	VA	270.52	-	AT/ABOVE 1140		CG 500 FT PER NM TO 1140
		-	-	VM	323.00	-			
OCIFR	414710.02N/0812223.63W	Y	-	IF	-	-	AT/ABOVE 3000		
WHARS	415129.70N/0810451.32W	Y	FB	TF	071.64	13.81	AT/BELOW 14000		
MYCAR	415537.85N/0804739.14W	Y	FB	TF	072.07	13.50			

