

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet, above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
COPAN	HUDIX (FB)	301.12 / 5.63	2100	LPV: DA LNAV/VNAV: DA LNAV: RW13	
HUDIX (IAF)	OLIRE (NOPT) (FB)	222.70 / 5.00	2100	CLIMB TO 2000 DIRECT ISICE AND HOLD.	
OLIRE (IF/IAF)	ROYOT (FB)	132.67 / 6.10	1800		
				ADDITIONAL FLIGHT DATA: HOLD SE, RT, 312.80 INBOUND. CHART FAS OBST: 32 TREE 275526N/0971318W CHART 315 TOWER 275620N/0971542W. CHART 270 KCTA 1030 275600N/0971536W. CHART A-632 B AND D. DISTANCE TO THLD FROM 250 HAT: 0.67 NM. CHART VDP AT 0.77 MILES TO RW13* *LNAV ONLY. WAAS CHANNEL # 78301 REFERENCE PATH ID: W13A CHART WAAS SYMBOL	

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
 2. HOLD NW OLIRE, RT, 132.67 INBOUND, 2100 FT. IN LIEU OF PT (IAF)
 3. FAC: 132.71 FAF: ROYOT DIST FAF TO MAP: 5.39 THLD: 5.39
 4. MIN. ALT: OLIRE 2100, ROYOT 1800, PUCIL/2.00 NM TO RW13 680*
 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
 6. MIN GS INCPT: 1800 GS ALT AT: ROYOT OM: MM: IM:
 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
 8. MSA FROM: RW13 2100

MAG VAR: 7E EPOCH YEAR: 1985

MINIMUMS															
TAKEOFF: ☒ STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: N A					STANDARD @				
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	268	1	250	268	1	250	268	1	250	268	1	250			
LNAV/VNAV DA	286	1	268	286	1	268	286	1	268	286	1	268			
LNAV MDA	300	1	282	300	1	282	300	1	282	300	1	282			
CIRCLING	520	1	502	520	1	502	520	1 1/2	502	580	2	562			

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING MUSTANG BEACH ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 49C (120F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 *LNAV ONLY
 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE INGLESIDE, TX	ELEVATION: 18 TDZE: 18 AIRPORT NAME: T P MC CAMPBELL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, AMDT 1 FEB 14 2008	SUP: AMDT: ORIG DATED 07/05/2007
---------------------------------	--	---------------------------------	--	--

7208-03

