

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
VOCCU (IAF)	ZEPEX (NOPT) (FB) (RNP 1.00)	270.83 / 5.00	2000	<b>LNAV: RW18</b>  <b>CLIMB TO 2000 DIRECT REPAE AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> <b>HOLD S, RT, 000.77 INBOUND.</b> <b>CHART FAS OBST: 459 100 FT TREE 331451N/0931215W</b> <b>CHART VDP AT 1.17 NM TO RW18.</b> <b>CINAY WP TO RW18: 3.05/40.</b>
OPAYA (IAF)	ZEPEX (NOPT) (FB) (RNP 1.00)	090.72 / 5.00	2000	
ZEPEX (IF/IAF)	WUROD (FB) (RNP 1.00)	180.77 / 6.01	2000	
WUROD (FAF)	CINAY/3.40 NM TO RW18 (FB) (RNP 0.30)	180.77 / 1.81		
CINAY/3.40 NM TO RW18 (SEE FORM 8260-10)	RW18 (MAP) (FO) (RNP 0.30)	180.77 / 3.40		

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD N ZEPEX, RT, 180.77 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
3. FAC: 180.77 FAF: WUROD DIST FAF TO MAP: 5.21 THLD: 5.21
4. MIN. ALT: ZEPEX 2000, WUROD 2000, CINAY/3.40 NM TO RW18 1400
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
7. GS ANGLE:        TCH: 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 1E EPOCH YEAR: 2020

**MINIMUMS**

TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>	ALTERNATE: N <input type="checkbox"/> A <input checked="" type="checkbox"/> X <input type="checkbox"/>														
CATEGORY >>>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	720	1	406	720	1	406	720	1 1/4	406		NA				
CIRCLING	760	1	441	780	1	461	780	1 1/2	461		NA				

NOTES:  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED USE EL DORADO ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.  
 CHART NOTE: VDP NA WITH EL DORADO ALTIMETER SETTING.  
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.



CITY AND STATE <b>MAGNOLIA, AR</b>	ELEVATION: 319 TDZE: 314 AIRPORT NAME: <b>RALPH C WEISER FIELD</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 18, ORIG-A</b> 17 AUGUST 2017	SUP: AMD T: <b>ORIG</b> DATED <b>09/30/2004</b>
---------------------------------------	--	-------------------------------------	---	---

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW18 (MAP)	719 MSL (CA)		
719 MSL	REPAAE (DF) (FO) (RNP 1.00)		2000

**TAA**

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	091/30 CW 271/30	091/20 CW 271/20	2400
2.	091/20 CW 271/20 (NOPT)	ZEPEX (IF/IAF)	2000
3.	271/30 CW 001/30	VOCCU (IAF)	2000
4.	001/30 CW 091/30	OPAYA (IAF)	2000



CITY AND STATE <b>MAGNOLIA, AR</b>	ELEVATION: 319 TDZE: 314 AIRPORT NAME: <b>RALPH C WEISER FIELD</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 18, ORIG-A</b> 17 AUGUST 2017	SUP:
				AMDT: <b>ORIG</b>
				DATED: <b>09/30/2004</b>