

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW30 CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 2000 DIRECT FRYED AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 249.89 INBOUND. FAS OBST: 224 AAO 293637N/0945943W DISTANCE TO THLD FROM 266 HATH: 0.71 NM. WAAS CHANNEL # 93928 REFERENCE PATH ID: W30A LTP HAE: -19.8 M											
PORRI (IAF)	ZEVOL (FB)	211.33 / 10.00	2000												
GROTN (IAF)	ZEVOL (FB)	031.21 / 10.00	2000												
ZEVOL (IF)	ENODE (FB)	301.27 / 7.00	1800												
ENODE (FAF)	RW30 (MAP) (FO)	301.22 / 5.45													
RW30 (MAP)	600 MSL	301.22	600												
600 MSL	FRYED (FO)		2000												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 5E EPOCH YEAR: 1990											
2. PROFILE STARTS AT ZEVOL															
3. FAC: 301.22 FAF: ENODE DIST FAF TO MAP: 5.45 THLD: 5.45															
4. MIN. ALT: ZEVOL 2000, ENODE 1800															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: 1800 GS ALT AT: ENODE 1800 OM: MM: IM:															
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR															
8. MSA FROM: RW30 3100															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	290	1	266	290	1	266	290	1	266						
LNAV/VNAV DA	344	1 1/8	320	344	1 1/8	320	344	1 1/8	320						
LNAV MDA	520	1	496	520	1	496	520	1 3/8	496						
CIRCLING	600	1	575	620	1	595	620	1 1/2	595			NA			
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: USE ELLINGTON FIELD ALTIMETER SETTING. CHART NOTE: STRAIGHT IN / CIRCLING RWY 30 PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE LA PORTE, TX			ELEVATION: 25 THRE: 24 AIRPORT NAME: LA PORTE MUNI			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30, AMDT 2 26 JULY 2012				SUP: AMDT: 1 DATED 12/22/2005			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PLANVIEW NOTE: RADAR REQUIRED.

QUALITY
CHECKED

CITY AND STATE LA PORTE, TX	ELEVATION: 25	THRE: 24	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30, AMDT 2 26 JULY 2012	SUP:
	AIRPORT NAME:				AMDT: 1
	LA PORTE MUNI				DATED: 12/22/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	T41
RUNWAY	RW30
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W30A
LTP/FTP LATITUDE	293959.1935N
LTP/FTP LONGITUDE	0950336.1240W
LTP/FTP ELLIPSOIDAL HEIGHT	-00198
FPAP LATITUDE	294051.9100N
FPAP LONGITUDE	0950458.6800W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1600
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

BE809747

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00074
FPAP ORTHOMETRIC HEIGHT	+00074

QUALITY
CHECKED

CITY AND STATE LA PORTE, TX	ELEVATION: 25 THRE: 24 AIRPORT NAME: LA PORTE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30, AMDT 2 26 JULY 2012	SUP:
				AMDT: 1
				DATED: 12/22/2005

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP T41 K4FR30	AGROTN 010GROTNK4EA0E	A	IF							18000		A JS	
SUSAP T41 K4FR30	AGROTN 020ZEVOLK4EA0EE	B	010TF			03120100		+ 02000				A JS	
SUSAP T41 K4FR30	APORRI 010PORRIK4EA0E	A	IF							18000		A JS	
SUSAP T41 K4FR30	APORRI 020ZEVOLK4EA0EE	B	010TF			21130100		+ 02000				A JS	
SUSAP T41 K4FR30	R 010ZEVOLK4EA0E	I	IF					+ 02000		18000		A JS	
SUSAP T41 K4FR30	R 020ENODEK4EA1E	F	051TF			30130070		+ 01800			RW30 K4PGA	JS	
SUSAP T41 K4FR30	R 020ENODEK4EA2WALPV			ALNAV/VNAV	ALNAV							JS	
SUSAP T41 K4FR30	R 030RW30 K4PG0GY	M	031TF			30120055		00064		-300		A JS	
SUSAP T41 K4FR30	R 040		0 M	CA		3012		+ 00600				A JS	
SUSAP T41 K4FR30	R 050FRYEDK4EA0EY	R	DF					+ 02000				A JS	
SUSAP T41 K4FR30	R 060FRYEDK4EA0EE	R	HM			24990040		+ 02000				A JS	

[illegible][illegible][illegible]

SUP:	
AMDT:	1
DATED:	12/22/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	GROTN	GROTN	010	IAF	IF		FB					
	GROTN	ZEVOL	020		TF		FB	1.0	031.2 (036.2T)	010.0	AA 02000	
	PORRI	PORRI	010	IAF	IF		FB					
	PORRI	ZEVOL	020		TF		FB	1.0	211.3 (216.3T)	010.0	AA 02000	
		ZEVOL	010	FACF	IF		FB				AA 02000	
		ENODE	020	FAF	TF		FB	0.5	301.3 (306.3T)	007.0	AA 01800	
		RW30	030	MAP	TF		FO	0.3	301.2 (306.2T)	005.5	AT 00064	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		301.2 (306.2T)		AA 00600	
	FRYED	050		DF	R	FO				AA 02000	
	FRYED	060		HM	R	FO		249.9 (254.9T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ENODE	N293645.55	W0945833.27	N2936.759	W09458.555
	FRYED	N294550.63	W0944846.68	N2945.844	W09448.778
	GROTN	N292431.48	W0945851.21	N2924.525	W09458.854
	PORRI	N294041.37	W0944517.33	N2940.690	W09445.289
	ZEVOL	N293236.60	W0945204.81	N2932.610	W09452.080
	RW30	N293959.19	W0950336.12	N2939.987	W09503.602

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW30	00024	40

QUALITY
9
CHECKED

CITY AND STATE LA PORTE, TX	ELEVATION: 25	THRE: 24	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 30, AMDT 2	AMDT: 1
	LA PORTE MUNI	RNAV		26 JULY 2012	DATED: 12/22/2005