

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
MQG VOR/DME	HENVO (TF) (FO) (RNP 2.00)	091.90 / 10.59	6300	<b>LPV: DA</b> <b>LNAV/VNAV: DA</b> <b>LNAV: RW26</b>  <b>CLIMB TO 7000 DIRECT GIYES AND ON TRACK 246.38 TO SEVER AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000.</b>  <b>ADDITIONAL FLIGHT DATA:</b> <b>HOLD W, LT, 071.46 INBOUND.</b> <b>CHART FAS OBST: 1688 TREE 462144N/1165702W</b> <b>CHART 2364 TREE 462000N/1164719W.</b> <b>CHART 2524 TREE 461946N/1164556W</b> <b>DISTANCE TO THLD FROM 200 HAT: 0.49 NM.</b> <b>CHART VDP AT 1.43 NM TO RW26*</b> <b>*LNAV ONLY.</b> <b>WAAS CHANNEL # 78012</b> <b>REFERENCE PATH ID: W26A</b> <b>LTP HAE: 418.7 M</b>
PETEZ (IAF)	HENVO (NOPT) (TF) (FB) (RNP 1.00)	174.10 / 6.42	5600	
ZATIP (IAF)	SAKME (TF) (FB) (RNP 1.00)	312.78 / 3.50	6200	
SAKME	HENVO (NOPT) (TF) (FB) (RNP 1.00)	312.75 / 4.20	5600	
HENVO (IF/IAF) (SEE FORM 8260-10)	FONDA (TF) (FB) (RNP 1.00)	264.08 / 3.23	5100	
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD E HENVO, RT, 264.08 INBOUND, 5600 FT. IN LIEU OF PT (IAF) 3. FAC: <u>263.98</u> FAF: <u>JANIG</u> DIST FAF TO MAP: <u>9.83</u> THLD: <u>9.83</u> 4. MIN. ALT: <b>HENVO 5600, FONDA 5100, JANIG 4700, GAGGO/4.90 NM TO RW26 3060*</b> 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>4700</u> GS ALT AT: <u>JANIG 4700</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>51.4</u> 34:1 IS CLEAR 8. MSA FROM: <b>RW26 7600</b>				MAG VAR: 15E                      EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1642	1/2	200	1642	1/2	200	1642	1/2	200	1642	1/2	200			
LNAV/VNAV DA	1962	1 1/4	520	1962	1 1/4	520	1962	1 1/4	520	1962	1 1/4	520			
LNAV MDA	1940	1/2	498	1940	1/2	498	1940	1	498	1940	1	498			
CIRCLING	2000	1	558	2000	1	558	2000	1 1/2	558	2160	2 1/4	718			

NOTES:  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 47C (116F). @ CAT D 800-2 1/4  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 \*LNAV ONLY  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MGQ VOR/DME ON V253 NORTHBOUND.  
 CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).



CITY AND STATE <b>LEWISTON, ID</b>	ELEVATION: 1442      TDZE: 1442 AIRPORT NAME: <b>LEWISTON-NEZ PERCE COUNTY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) Y RWY 26, ORIG-B</b> 17 AUGUST 2017	SUP: AMDT: <b>ORIG-A</b> DATED <b>06/03/2010</b>
---------------------------------------	--	-------------------------------------	--	--

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
FONDA	JANIG (TF) (FB) (RNP 1.00)	264.03 / 2.77	4700
JANIG (FAF)	GAGGO/4.90 NM TO RW26 (TF) (FB) (RNP 0.30)	263.98 / 4.93	
GAGGO/4.90 NM TO RW26	RW26 (MAP) (TF) (FO) (RNP 0.30)	263.98 / 4.90	
RW26 (MAP)	1642 MSL (CA)	263.98	
1642 MSL	GIYES (DF) (FB) (RNP 1.00)		
GIYES	SEVER (TF) (FO) (RNP 1.00)	246.26 / 14.39	7000



CITY AND STATE <b>LEWISTON, ID</b>	ELEVATION: 1442 TDZE: 1442 AIRPORT NAME: <b>LEWISTON-NEZ PERCE COUNTY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) Y RWY 26, ORIG-B</b> 17 AUGUST 2017	SUP:
				AMDT: <b>ORIG-A</b>
				DATED: <b>06/03/2010</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KLWS
RUNWAY	RW26
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W26A
LTP/FTP LATITUDE	462215.7060N
LTP/FTP LONGITUDE	1170007.5190W
LTP/FTP ELLIPSOIDAL HEIGHT	+04187
FPAP LATITUDE	462229.3300N
FPAP LONGITUDE	1170214.6900W
THRESHOLD CROSSING HEIGHT (TCH)	00051.4
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER EDE6E667

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K1
LTP ORTHOMETRIC HEIGHT	+04395
FPAP ORTHOMETRIC HEIGHT	+04395



CITY AND STATE <b>LEWISTON, ID</b>	<b>ELEVATION: 1442</b>	<b>TDZE: 1442</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) Y RWY 26, ORIG-B</b> 17 AUGUST 2017	SUP:
	AIRPORT NAME: <b>LEWISTON-NEZ PERCE COUNTY</b>				AMDT: <b>ORIG-A</b>
					DATED: <b>06/03/2010</b>