Federal Aviation Administration

Transmittal Letter 20-07

February 7, 2020

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC I	DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/26/2	2020	MN	Albert Lea	Albert Lea Muni	0/1832	2/3/2020	VOR RWY 17, Amdt 1A

AIRAC Date: 26 MARCH 2020

FDC 0/1832 AEL IAP ALBERT LEA MUNI. ALBERT LEA. MN. VOR RWY 17. AMDT 1A... S-17 MDA 2020/HAT 760 ALL CATS, VISIBILITY CAT C/D 2. CIRCLING MDA 2020/HAA 759 ALL CATS, VISIBILITY CAT B 1 1/4, CAT C 2 1/4, CAT D 2 1/2. DELETE WAKNA FIX MINIMUMS. EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED, DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUSTIN ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET: INCREASE S-17 CAT C/D VISIBILITY 1/4 MILE, AND WAKNA FIX MINIMUMS S-17 CAT C/D VISIBILITY 1/8 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUSTIN ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE S-17 CAT C/D VISIBILITY 1/2 SM. DELETE NOTE: CIRCLING TO RWY 5/23 NA AT NIGHT. CHART NOTE: CIRCLING RWY 5, 23 NA AT NIGHT. DELETE MAP: 4.64 MILES AFTER GROVY INT/5.00 DME OR AT JULBU/0.36 DME FIX. CHART MAP: JULBU/0.36 DME. DELETE FAS OBSTS: 1490 AAO 434415N/0933421W AND 1550 AAO 434626N/0932334W. CHART FAS OBST: 1712 WINDMILL 434622N/0932437W. THIS IS VOR RWY 17, AMDT 1B. 2001081629-PERM.