

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23					Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
TERMINAL ROUTES					MISSED APPROACH				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 6.97 MILES AFTER SLN VORTAC OR AT SLN 6.97 DME FIX CLIMB TO 3400 DIRECT SL LOM AND HOLD. ADDITIONAL FLIGHT DATA: ✓ HOLD S, RT, 352.62 INBOUND. ✓ CHART FAS OBST: 1487 OL TWR 385028N/0973950W ✓ CHART ADA EAST, WEST MOA. ✓ CHART R-3601A. ✓ CHART VDP AT 5.52 DME; ✓ DISTANCE VDP TO THLD 1.45 MILES. ✓ CHART SLN R-075 AT ZITIK. ✓ CHART SLN R-260 AT HETAB.					
HETAB/SLN 7.00 DME CW (IAF)	WEGIV/SLN 7.00 DME (NOPT)	7.00 DME ARC	3000						
ZITIK/SLN 7.00 DME CCW (IAF)	WEGIV/SLN 7.00 DME (NOPT)	7.00 DME ARC	3000						
WEGIV/SLN 7.00 DME (IF)	SLN VORTAC	182.52 / 7.00	3000						

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)			
2. <u>HOLD N SLN VORTAC, RT, 182.52 INBOUND, 3000 FT. IN LIEU OF PT (IAF)</u>			
3. FAC <u>182.52</u> FAF <u>SLN VORTAC</u>		DIST FAF TO MAP <u>6.97</u> THLD <u>6.97</u>	
4. MIN. ALT <u>SLN VORTAC 3000, JOTIN/SLN 4.57 DME 1860*</u>			
8. MSA FROM: <u>SLN VORTAC 3400</u>		MAG VAR: <u>7E</u> EPOCH YEAR: <u>1990</u>	

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-17	1860	3/4	614	1860	3/4	614	1860	1 3/4	614	1860	2	614	1860	2 1/4	614
CIRCLING	1860	1	572	1860	1	572	1860	1 3/4	572	1860	2	572	1920	2 1/4	632

JOTIN FIX MINIMUMS															
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-17	1760	3/4	514	1760	3/4	514	1760	1 1/2	514	1760	1 3/4	514	1760	1 3/4	514
CIRCLING	1820	1	532	1820	1	532	1840	1 1/2	552	1840	2	552	1920	2 1/4	632

NOTES:
 CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO CAT C/D/E.
 CHART NOTE: CIRCLING NA FOR CAT D/E SOUTHWEST OF RWY 12-30.
 CHART NOTE: ADF REQUIRED.
 * 1960 WHEN USING MCPHERSON ALTIMETER SETTING.
 SEE 8260-10

CITY AND STATE
SALINA, KS

ELEVATION: 1288 TDZE: 1246
 AIRPORT NAME:
SALINA MUNI

FACILITY IDENTIFIER:
SLN

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR RWY 17, AMDT 2
NOV 20 2008

SUP
 AMDT **1A**
 DATE **02/16/2006**

CHECKED

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MCPHERSON ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND CAT C/D/E VISIBILITY 1/4 MILE AND INCREASE JOTIN FIX MINIMUMS S-17

CAT C/D VISIBILITY 1/4 MILE, CAT E VISIBILITY 1/2 MILE, CIRCLING CAT C/E VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WHEN USING MCPHERSON ALTIMETER SETTING.

CITY AND STATE

SALINA, KS

ELEVATION: 1288 TDZE: 1246

AIRPORT NAME:

SALINA MUNI

FACILITY
IDENTIFIER:

SLN

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

VOR RWY 17, AMDT 2

NOV 20 2008

SUP:

AMDT: 1A

DATED: 02/16/2006

CHECKED