

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW26L CLIMB TO 7000 DIRECT MERTZ AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, LT, 290.00 INBOUND. FAS OBST: 4850 AAO 381751N/1042157W CHART 4986 TOWER 381714N/1042050W CHART A-639A. DISTANCE TO THLD FROM 200 HAT: 0.47 NM. CHART VDP AT 1.41 MILES TO RW26L* *LNAV ONLY. WAAS CHANNEL # 53531 REFERENCE PATH ID: W26A CHART CIRCLING ICON. LTP HAE: 1397.3 M					
PUB VORTAC		HELER (FO)		082.11 / 10.00				7200							
DRAKE		BONUH (FB)		136.47 / 15.67				7700							
STAXX		REDHI (FB)		345.84 / 12.91				7000							
VIGIL		REDHI (FB)		035.72 / 21.59				7900							
BONUH (IAF)		HELER (NOPT) (FB)		170.45 / 6.00				7000							
ORWAY (IAF)		HELER (NOPT) (FB)		270.13 / 7.74				7000		(SEE FORM 8260-10)					
REDHI (IAF)		HELER (NOPT) (FB)		345.83 / 6.00				7000							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E HELER, RT, 260.45 INBOUND, 7000 FT. IN LIEU OF PT (IAF) 3. FAC: 260.37 FAF: JIKTA _____ DIST FAF TO MAP: 5.94 THLD: 5.94 4. MIN. ALT: HELER 7000, JIKTA 6600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 6600 GS ALT AT: JIKTA 6600 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 60.0 34:1 IS CLEAR 8. MSA FROM: RW26L 9300										MAG VAR: 8E		EPOCH YEAR: 2015			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	4859	3/4	200	4859	3/4	200	4859	3/4	200	4859	3/4	200			
LNAV/VNAV DA	4979	1	320	4979	1	320	4979	1	320	4979	1	320			
LNAV MDA	5100	1	441	5100	1	441	5100	1 3/8	441	5100	1 3/8	441			
CIRCLING	5340	1	611	5340	1	611	5560	2 1/2	831	5800	3	1071			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -22C (-7F) OR ABOVE 47C (116F). @ CAT C 900-2 1/2, CAT D 1100-3 CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART SPEED ICON IN PLANVIEW AT HELER : MAX 210 KIAS.															
CITY AND STATE		ELEVATION: 4729 TDZE: 4659		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
PUEBLO, CO		AIRPORT NAME: PUEBLO MEMORIAL				RNAV (GPS) RWY 26L, AMDT 1, 05/26/2016				AMDT: ORIG					
										DATED 06/27/2013					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HELER (IF/IAF)	JIKTA (FB)	260.45 / 6.15	6600
JIKTA (FAF)	RW26L (MAP) (FO)	260.37 / 5.94	
RW26L (MAP)	4859 MSL	260.37	
4859 MSL	MERTZ (FO)		7000

QUALITY
16
CHECKED

CITY AND STATE
PUEBLO, CO

ELEVATION: 4729 TDZE: 4659
AIRPORT NAME:
PUEBLO MEMORIAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 26L, AMDT 1, 05/26/2016

SUP:
AMDT: ORIG
DATED: 06/27/2013

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPUB
RUNWAY	RW26L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W26A
LTP/FTP LATITUDE	381716.7700N
LTP/FTP LONGITUDE	1042824.6700W
LTP/FTP ELLIPSOIDAL HEIGHT	+13973
FPAP LATITUDE	381713.6540N
FPAP LONGITUDE	1043036.2300W
THRESHOLD CROSSING HEIGHT (TCH)	00060.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

0F9269E5

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+14169
FPAP ORTHOMETRIC HEIGHT	+14169

QUALITY
16
CHECKED

CITY AND STATE

PUEBLO, CO

ELEVATION: 4729

TDZE: 4659

AIRPORT NAME:

PUEBLO MEMORIAL

 FACILITY
IDENTIFIER:
RNAV

 PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 26L, AMDT 1, 05/26/2016

SUP:

AMDT: ORIG

DATED: 06/27/2013

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KPUB

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
DRAKE	010	DRAKE	IF	FB										E
DRAKE	020	BONUH	TF	FB	2.0	136.5						AA 07700		E A
DRAKE	030	HELER	TF	FB	1.0	170.5						AA 07000		EE B
ORWAY	010	ORWAY	IF	FB										E A
ORWAY	020	HELER	TF	FB	1.0	270.1						AA 07000		EE B
PUB	010	PUB	IF	FB										V
PUB	020	HELER	TF	FO	2.0	082.1						AA 07200		EY
PUB	030	HELER	HF	FO		260.5			R			AA 07000		EE A
STAXX	010	STAXX	IF	FB										E
STAXX	020	REDHI	TF	FB	2.0	345.8						AA 07000		E A
STAXX	030	HELER	TF	FB	1.0	345.8						AA 07000		EE B
VIGIL	010	VIGIL	IF	FB										E
VIGIL	020	REDHI	TF	FB	2.0	035.7						AA 07900		E A
VIGIL	030	HELER	TF	FB	1.0	345.8						AA 07000		EE B
	010	HELER	IF	FB								AA 07000		E I
	020	JIKTA	TF	FB	1.0	260.5				RW26L		AA 06600		E F
	030	RW26L	TF	FO	0.3	260.4		3.00				AT 04709		GY M
	040	CA	FB			260.4						AA 04859		M
	050	MERTZ	DF	FO								AA 07000		EY
	060	MERTZ	HM	FO		290.0			L			AA 07000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
PUB	N381739.32	W1042546.01
BONUH	N382337.55	W1041316.30
DRAKE	N383624.05	W1042451.18
HELER	N381737.43	W1041303.92
JIKTA	N381727.17	W1042052.36
MERTZ	N381701.63	W1043849.19
ORWAY	N381632.08	W1040320.14
REDHI	N381139.04	W1041214.76
STAXX	N375848.29	W1041029.43
VIGIL	N375603.37	W1043110.43

RUNWAYS

QUALITY
15
CHECKED

CITY AND STATE PUEBLO, CO	ELEVATION: 4729	TDZE: 4659	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 26L, AMDT 1, 05/26/2016	SUP:
	AIRPORT NAME: PUEBLO MEMORIAL				AMDT: ORIG
					DATED: 06/27/2013

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH	
RW26L	N381716.77	W1042824.67	04649	60.0	
QUALITY 15 CHECKED					
CITY AND STATE PUEBLO, CO	ELEVATION: 4729 TDZE: 4659 AIRPORT NAME: PUEBLO MEMORIAL		FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 26L, AMDT 1, 05/26/2016	SUP: AMDT: ORIG DATED: 06/27/2013