

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
ADOBE	KEFZU (FB)	122.39 / 21.01	3100	LPV: DA LNAV/VNAV: DA LNAV: RW20	
VASTY	BECAT (FB)	015.28 / 14.63	3100	CLIMB TO 3300 DIRECT OXULY AND HOLD.	
KEFZU (IAF)	EFAKU (FB)	113.92 / 5.00	3100		
BECAT (IAF)	EFAKU (FB)	294.02 / 5.00	3100		
EFAKU (IF)	YEPUV (FB)	203.97 / 6.10	3000		
				ADDITIONAL FLIGHT DATA: HOLD SW, RT, 023.82 INBOUND. CHART FAS OBST: 1309 TREE 341406N/0991706W CHART FAS OBST: 1319 TREE 341354N/0991724W DISTANCE TO THLD FROM 250 HAT: 0.67 NM. WAAS CHANNEL # 63018 REFERENCE PATH ID: W20A	

- PT NA SIDE OF COURSE          OUTBOUND          FT WITHIN          MILES OF          (IAF)
- PROFILE STARTS AT EFAKU
- FAC: 203.93 FAF: YEPUV DIST FAF TO MAP: 5.28 THLD: 5.28
- MIN. ALT: EFAKU 3100, YEPUV 3000, VIDUY/1.30 NM TO RW20 1700\*
- DIST TO THLD FROM OM:          MM:          IM:          150 HAT:          100 HAT:          GS ANT:
- MIN GS INCPT: 3000 GS ALT AT: YEPUV 3000 OM:          MM:          IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
- MSA FROM: RW20 3400

MAG VAR: 8E EPOCH YEAR: 1980

MINIMUMS																
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: NA	STANDARD @					
CATEGORY ==>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1509	1	250	1509	1	250	1509	1	250		NA					
LNAV/VNAV DA	1585	1 1/4	326	1585	1 1/4	326	1585	1 1/4	326		NA					
LNAV MDA	1580	1	321	1580	1	321	1580	1	321		NA					
CIRCLING	1660	1	395	1720	1	455	1720	1 1/2	455		NA					

NOTES:  
 CHART NOTE: BARO-VNAV NA WHEN USING FREDERICK ALTIMETER SETTING.  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F).  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE <b>VERNON, TX</b>	ELEVATION: 1265 TDZE: 1259 AIRPORT NAME: <b>WILBARGER COUNTY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 20, ORIG 29 JUL 2010</b>	SUP: AMDT: <b>NONE</b> DATED
-------------------------------------	--	-------------------------------------	--	------------------------------------

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES CONT.**

**CHART PROFILE NOTE: VGS1 AND RNAV GLIDEPATH NOT COINCIDENT.**

**\*LNAV ONLY**

**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FREDERICK ALTIMETER SETTING: INCREASE ALL DA/MDA 40 FEET.**



CITY AND STATE <b>VERNON, TX</b>	ELEVATION: 1265 TDZE: 1259 AIRPORT NAME: <b>WILBARGER COUNTY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 20, ORIG 29 JUL 2010</b>	SUP:
				AMDT: <b>NONE</b>
				DATED:

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	F05
RUNWAY	RW20
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W20A
LTP/FTP LATITUDE	341354.1975N
LTP/FTP LONGITUDE	0991643.9145W
LTP/FTP ELLIPSOIDAL HEIGHT	+03542
FPAP LATITUDE	341238.4200N
FPAP LONGITUDE	0991740.6800W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1200
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

**CRC REMAINDER** 6F0F0AAF

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+03826
FPAP ORTHOMETRIC HEIGHT	+03826

QUALITY  
CHECKED

CITY AND STATE VERNON, TX	ELEVATION: 1265 TDZE: 1259 AIRPORT NAME: WILBARGER COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, ORIG 29 JUL 2010	SUP:
				AMDT: NONE
				DATED:



