

**Federal Aviation
Administration**

Transmittal Letter 24-23

September 13, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/31/2024	WI	Platteville	Platteville Muni	4/2636	7/29/2024	RNAV (GPS) RWY 33, Orig-A

AIRAC Date: 31 OCTOBER 2024

FDC 4/2636 PVB IAP PLATTEVILLE MUNI, PLATTEVILLE, WI. RNAV (GPS) RWY 33, ORIG-A... PBN
REQUIREMENTS NOTE: RNP APCH - GPS. DELETE NOTE: DME/DME RNP-0.3 NA. CHANGE NOTE TO
READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C.
CHART NOTE: CIRCLING RWY 7, 25 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER NOTE
RECEIVED, USE DBQ ALTIMETER SETTING AND INCREASE LPV DA TO 1331 FEET; INCREASE LNAV/VNAV
DA TO 1497 FEET AND ALL CATS VISIBILITIES 1/4 SM; INCREASE ALL MDAS 60 FEET, INCREASE LNAV
AND CIRCLING CAT C VISIBILITIES 1/4 SM. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING DBQ
ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 33, ORIG-B. 2406241722-PERM