Federal Aviation Administration

Transmittal Letter 20-07

February 7, 2020

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/26/2020	IL	Olney- Noble	Olney-Noble	0/2262	1/16/2020	RNAV (GPS) RWY 11, Amdt 1B

AIRAC Date: 26 MARCH 2020

FDC 0/2262 OLY IAP OLNEY-NOBLE, OLNEY-NOBLE, IL. RNAV (GPS) RWY 11, AMDT 1B... DELETE NOTE: NIGHT LANDING RWY 03, 21, 29 NA. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENT NOTE: RNP APCH. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE ALTIMETER SETTING AND INCREASE ALL DA 126 FEET, MDA 140 FEET; INCREASE LPV VISIBILITY 1/4 MILE ALL CATS, LNAV/VNAV VISIBILITY 3/4 MILE ALL CATS, LNAV VISIBILITY 3/8 MILE CAT C/D AND CIRCLING VISIBILITY 1/2 MILE CAT C/D. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE ALTIMETER SETTING AND INCREASE ALL DAS 126 FEET, MDAS 140 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, LNAV CAT C/D 3/8 SM AND CIRCLING CAT C 1/4 SM AND CAT D 1/2 SM. THIS IS RNAV (GPS) RWY 11, AMDT 1C, 2001091620-PERM