

**Federal Aviation
Administration**

Transmittal Letter 21-13

April 30, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/17/2021	TX	Eagle Lake	Eagle Lake	1/6411	4/6/2021	VOR RWY 17, Amdt 5A

AIRAC Date: 17 JUNE 2021

FDC 1/6411 ELA IAP EAGLE LAKE, EAGLE LAKE, TX. VOR RWY 17, AMDT 5A... S-17 CAT C
VIS 1 3/8. CIRCLING CAT C MDA 1040/HAA 856, CAT C VIS 2 1/2. CHART NOTE: CIRCLING
RWY 35 NA AT NIGHT. CHART VDP AT 2.06 DME, DISTANCE VDP TO THRESHOLD 1.34
NM. CHART NOTE: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT
AUTHORIZED. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
SUGAR LAND RGNL ALTIMETER SETTING. CHART NOTE: VDP NA WHEN USING
WHARTON ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT
RECEIVED, USE WHARTON ALTIMETER SETTING AND INCREASE ALL MDA 80 FT AND S-
17 AND CIRCLING CAT C VISIBILITY 1/4 SM. THIS IS VOR RWY 17, AMDT 5B. 2103171814-
PERM