

**FEDERAL AVIATION ADMINISTRATION
 FLIGHT STANDARDS SERVICE
 VOR STANDARD INSTRUMENT APPROACH PROCEDURE
 TITLE 14 CFR PART 97.23**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT AINSWORTH RGNL	AIRPORT ID KANW	PROCEDURE NAME VOR RWY 35	ORIGINAL/AMENDMENT 4A	CITY AINSWORTH	STATE NE	
AIRPORT ELEVATION 2589	TDZE 2589	SUPERSEDED VOR RWY 35	ORIGINAL/AMENDMENT 4	DATED 01/18/2007	MAG VAR 9E	EPOCH YEAR 1985
FACILITY ANW	COORDINATES OF FACILITIES	ACTUAL EFFECTIVE DATE 26 MARCH 2020	REQUIRED EFFECTIVE DATE ROUTINE	CANCEL/SUSPEND		

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE

MISSED APPROACH

MAP:
ANW VOR/DME

MISSED APPROACH INSTRUCTIONS:
CLIMB TO 3500 THEN CLIMBING LEFT TURN TO 6000 DIRECT ANW VOR/DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT R SIDE OF COURSE 187.64 OUTBOUND 4500 FT WITHIN 10 MILES OF ANW VOR/DME (IAF)
- 2.
3. FAC: 007.64 FAF: DIST FAF TO MAP: DIST FAF TO THLD:
4. MIN ALT: BIYAG/2.28 DME 3300
8. MSA FROM: ANW VOR/DME 090-270 5100, 270-090 4300

EQUIPMENT REQUIREMENTS NOTES:

NOTES:
WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.
FOR INOPERATIVE ALS, INCREASE BIYAG FIX MINIMUMS S-35 CAT D VISIBILITY TO 1 1/4.



ADDITIONAL FLIGHT DATA:

CHART 6000 PRIOR TO ANW VOR/DME IN PROFILE VIEW.
 BIYAG TO RW35: 2.99/45.
 CHART VDP AT 1.30 DME
 DISTANCE VDP TO THLD 1.15 NM
 CHART FAS OBST: 2739 TREE 423221N/1000042W.
 FAC CROSSES RWY C/L EXTENDED 5197 FT FROM THLD.
 HOLD S, LT, 008.00 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA STANDARD - CAT D 800-2 1/4

CATEGORY:	A			B			C			D			E			
	FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-35	3300	1/2	711	3300	1/2	711	3300	1 1/2	711	3300	1 3/4	711				
CIRCLING	3300	1	711	3300	1	711	3300	2	711	3300	2 1/4	711				
BIYAG FIX MINIMUMS (DME REQUIRED)																
S-35	3000	1/2	411	3000	1/2	411	3000	3/4	411	3000	1	411				
CIRCLING	3000	1	411	3040	1	451	3040	1 1/2	451	3140	2	551				

CHANGES - REASONS

ALL REFERENCE TO ABEKE CHANGED TO BIYAG - ABEKE 8260-2 WAS UPDATED 04/15/2004 WITH THE NAME CHANGED FROM ABEKE TO BIYAG.
 INOPERATIVE COMPONENTS AND VISUAL AIDS, UPDATED THE WORD MALSR TO ALS - CURRENT CRITERIA WORDING.
 DELETED NOTE: * MAINTAIN 6000 UNTIL ESTABLISHED ON PROCEDURE TURN OUTBOUND - REPLACED IN ADDITIONAL FLIGHT DATA SECTION WITH CHART 6000 PRIOR TO ANW VOR/DME IN PROFILE VIEW.
 BIYAG FIX MINIMUMS ADDED (DME REQUIRED) - EQUIPMENT REQUIREMENTS NOTE.
 ADDED NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA - SUITABLE BACKUP ALTIMETER SOURCE IS NOT AVAILABLE.
 01/02/20: THIS IS A CORRECTED COPY OF THE FORM DEVELOPED ON 08/14/19.
 1. ADDED "ROUTINE" TO REQUIRED EFFECTIVE DATE.

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA OTHER: ZDV, ARPT MGR

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
 FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

DEVELOPED BY
 DEANNA M. FIELDS

Digitally signed by
DEANNA M FIELDS

MARK D ADAMS
 Aug 14, 2019

OFFICE
 AJV-A412

DATE
 07/22/2019

APPROVED BY
 JULIE MORGAN

Jul 30, 2019 Digitally signed by
MARK D ADAMS
 Aug 14, 2019

OFFICE
 AJV-A410

DATE

TITLE
 MANAGER

