

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
DODAH (IAF)	KINLY OM (NOPT)	024.82 / 1.01 (HDG) & 061.88 / 6.47 (I-GUP)	8200

MAP: 5.09 NM AFTER KINLY OM

CLIMB TO 7500 THEN CLIMBING RIGHT TURN TO 9000 DIRECT GUP VORTAC AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SW, RT, 047.09 INBOUND.
CHART FAS OBST: 7099 TREE 352841N/1085222W.
KINLY OM TO RW06: 3.13/45.

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- TEARDROP R-226 (GUP VORTAC) (IAF) OUTBOUND WITHIN 10 NM, 9000, 061.88 (I-GUP) INBOUND, 8200 TO KINLY OM.
- FAC 061.88 FAF KINLY OM DIST FAF TO MAP 5.09 THLD 5.09
- MIN. ALT KINLY OM 8200
- MSA FROM: GUP VORTAC 180-270 8900, 270-180 10400

MAG VAR: 12E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-06	7280	1	815	7280	1 1/4	815	7280	2 1/2	815	7280	2 3/4	815			
CIRCLING	7280	1	808	7280	1 1/4	808	7280	2 1/2	808	7360	3	888			

NOTES:
CHART NOTE: RWY 6 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.



CITY AND STATE GALLUP, NM	ELEVATION: 6472 TDZE: 6465 AIRPORT NAME: GALLUP MUNI	FACILITY IDENTIFIER: I-GUP	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC RWY 6, AMDT 3C 24 MAY 2018	SUP AMDT 3B DATE 08/18/1994
------------------------------	--	-------------------------------	---	-----------------------------------