

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ENEYA (IAF)	MODPY (NOPT) (FB)	277.66 / 5.00	4400	LNAV: RW19
PIVEE (IAF)	MODPY (NOPT) (FB)	097.52 / 5.00	4400	
MODPY (IF/IAF)	AMDIZ (FB)	187.59 / 6.26	3400	CLIMB TO 4400 DIRECT HEMED AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD S, RT, 007.51 INBOUND. CHART FAS OBST: 2071 TOWER 420820N/0980159W CHART 2119 TREE 421133N/0975933W. AMDIZ TO RW19: 3.04/41. CHART O'NEILL MOA

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N MODPY, RT, 187.59 INBOUND, 4400 FT. IN LIEU OF PT (IAF)
- FAC: 187.57 FAF: AMDIZ DIST FAF TO MAP: 5.04 THLD: 5.04
- MIN. ALT: MODPY 4400, AMDIZ 3400
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 5E

EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2380	1	618	2380	1	618		NA			NA				
CIRCLING	2380	1	606	2440	1	666		NA			NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: USE ALBION ALTIMETER SETTING; WHEN NOT RECEIVED, USE NORFOLK ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.



CITY AND STATE NELIGH, NE	ELEVATION: 1774 TDZE: 1762	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 17 DEC 2009	SUP:
	AIRPORT NAME: ANTELOPE COUNTY			AMDT: NONE
				DATED

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	098/30 CW 278/30 (NOPT)	MODPY (IF/IAF) (FB)	4400
2.	278/30 CW 008/30	ENEYA (IAF) (FB)	4400
3.	008/30 CW 098/30	PIVEE (IAF) (FB)	4400

CITY AND STATE

NELIGH, NE

ELEVATION: 1774 TDZE: 1762

AIRPORT NAME:

ANTELOPE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, ORIG

17 DEC 2009

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE NELIGH, NE	ELEVATION: 1774 TDZE: 1762 AIRPORT NAME: ANTELOPE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 17 DEC 2009	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ENEYA	ENEYA	010	IAF	IF		FB				
	ENEYA	MODPY	020		TF		FB	1.0	277.7(283T)	005.0	04400
	MODPY	MODPY	010	IAF	HF	R	FO		187.6(193T)	005.0	04400
	PIVEE	PIVEE	010	IAF	IF		FB				
	PIVEE	MODPY	020		TF		FB	1.0	097.5(103T)	005.0	04400
		MODPY	010	FACF	IF		FB				04400
		AMDIZ	020	FAF	TF		FB	0.5	187.6(193T)	006.3	03400
		RW19	030	MAP	TF		FO	0.3	187.6(193T)	005.0	01772

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	HEMED	040		DF		FO	1.0			04400
	HEMED	050		HM	R	FO	2.0	007.5(013T)	005.0	04400

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AMDIZ	N421149.63	W0980047.68	N4211.827	W09800.795
	ENEYA	N421650.65	W0975223.17	N4216.844	W09752.386
	HEMED	N415522.30	W0980542.40	N4155.372	W09805.707
	MODPY	N421756.25	W0975857.60	N4217.938	W09758.960
	PIVEE	N421901.48	W0980532.25	N4219.025	W09805.538
	RW19	N420654.24	W0980216.12	N4206.904	W09802.269

RUNWAY DATA	RWY	THRESHOLD	TCH
		ELEVATION	
	RW19	01731	41

QUALITY
CHECKED

CITY AND STATE NELIGH, NE	ELEVATION: 1774 TDZE: 1762	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 17 DEC 2009	SUP:
	AIRPORT NAME: ANTELOPE COUNTY			AMDT: NONE
	DATED:			