

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BAYJY (IAF)	JASER (NOPT) (FB)	082.98 / 5.09	3800
PRADO (IAF)	JASER (NOPT) (FB)	034.77 / 6.71	3800
JASER (IF/IAF)	UZOHO (FB)	091.60 / 3.96	3200
UZOHO	HASIV (FB)	091.66 / 3.95	2700

LNAV: RW06

CLIMBING RIGHT TURN TO 3200 DIRECT PDZ VORTAC AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD E, RT, 258.00 INBOUND.
FAS OBST: 1719 AAO 335638N/1173041W
CHART RIVERSIDE MUNI ASOS
HASIV TO RW06: 3.05/30

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD W JASER, RT, 091.60 INBOUND, 3800 FT. IN LIEU OF PT (IAF)
- FAC: 063.68 FAF: HASIV DIST FAF TO MAP: 5.93 THLD:
- MIN. ALT: JASER 3800, UZOHO 3200, HASIV 2700
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH:
- MSA FROM: RW06 12300

MAG VAR: 13E EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: <input type="checkbox"/> STANDARD <input checked="" type="checkbox"/> SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A <input checked="" type="checkbox"/>															
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	1860	1 1/4	1093	1960	1 1/2	1193		NA			NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: USE RIVERSIDE MUNI ALTIMETER SETTING; WHEN NOT RECEIVED, USE ONTARIO ALTIMETER
 SEE 8260-10



CITY AND STATE RIVERSIDE/RUBIDOUX, CA	ELEVATION: 767 TDZE: AIRPORT NAME: FLABOB	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 25 AUG 2011	SUP: AMDT: NONE DATED
---	--	-------------------------------------	---	------------------------------------

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.
SETTING AND INCREASE ALL MDA 60FT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT PRADO ON V16-370 WESTBOUND, AND FOR ARRIVALS AT BAYJY ON V186 WESTBOUND.



CITY AND STATE RIVERSIDE/RUBIDOUX, CA	ELEVATION: 767 TDZE: AIRPORT NAME: FLABOB	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, ORIG 25 AUG 2011	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3	
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012													

	SUSAP KRIRK2SRW06 K2PG										0	18018012325		M



CITY AND STATE RIVERSIDE/RUBIDOUX, CA	ELEVATION: 767 TDZE: AIRPORT NAME: FLABOB	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 25 AUG 2011	SUP:
				AMDT: NONE
				DATED: