

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE ALTIMETER SETTING: INCREASE LPV DA TO 719 FEET AND ALL CATS VISIBILITY 1/8 MILE; INCREASE LNAV/VNAV DA TO 734 FEET AND ALL CATS VISIBILITY 1/4 MILE; INCREASE ALL MDA 60 FEET AND LNAV CATS C/D AND CIRCLING CATS C/D VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING EVANSVILLE ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	326/30 CW 146/30 (NOPT)	FOLAB (IF/IAF) (FB)	3000
2.	146/30 CW 326/30	FOLAB (IF/IAF) (FO)	3000

CITY AND STATE

OWENSBORO, KY

ELEVATION: 407

THRE: 405

AIRPORT NAME:

OWENSBORO-DAVIESS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO / AMDT NO / EFFECTIVE DATE:

RNAV (GPS) RWY 6, AMDT 1

10 JANUARY 2013

SUP: RNAV (GPS) RWY 5

AMDT: ORIG

DATED: 09/30/2004

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KOWB
RUNWAY	RW06
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W06A
LTP/FTP LATITUDE	374409.7240N
LTP/FTP LONGITUDE	0871022.8655W
LTP/FTP ELLIPSOIDAL HEIGHT	+00927
FPAP LATITUDE	374504.6800N
FPAP LONGITUDE	0870854.3800W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

3B59A6F0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+01235
FPAP ORTHOMETRIC HEIGHT	+01235

CITY AND STATE

OWENSBORO, KY

ELEVATION: 407

THRE: 405

AIRPORT NAME:

OWENSBORO-DAVIESS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 6, AMDT 1

10 JANUARY 2013

SUP: RNAV (GPS) RWY 5

AMDT: ORIG

DATED: 09/30/2004

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KOWBK5FR06	AFOLAB	010FOLABK5EA0EE	AR	HF		05590040		+ 03000	18000			A	JS
SUSAP KOWBK5FR06	R	010FOLABK5EA0E	I	IF				+ 03000	18000			A	JS
SUSAP KOWBK5FR06	R	020APUDYK5EA1E	F	051TF		05590061		+ 02100				A	JS
SUSAP KOWBK5FR06	R	020APUDYK5EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KOWBK5FR06	R	021NASCIK5EA0E	S	031TF		05590027		V 0124001246		-300		A	JS
SUSAP KOWBK5FR06	R	030RW06	K5PGOGY	M 031TF		05600025		00450		-300		A	JS
SUSAP KOWBK5FR06	R	040		O M CA		0560		+ 00660				A	JS
SUSAP KOWBK5FR06	R	050CINLIK5EA0EY		DF				+ 03000				A	JS
SUSAP KOWBK5FR06	R	060CINLIK5EA0EE	R	HM		23610040		+ 03000				A	JS

[illegible]FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	FOLAB	FOLAB	010	IAF	HF	R	FO		055.9 (051.9T)	004.0	AA 03000	
		FOLAB	010	FACF	IF		FB				AA 03000	
		APUDY	020	FAF	TF		FB	0.5	055.9 (051.9T)	006.1	AA 02100	
		NASCI	021	SDF	TF		FB	0.3	055.9 (051.9T)	002.7	AA 01240	GS 01246
		RW06	030	MAP	TF		FO	0.3	056.0 (052.0T)	002.5	AT 00450	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		056.0 (052.0T)		AA 00660	
	CINLI	050		DF		FO				AA 03000	
	CINLI	060		HM	R	FO		236.1 (232.1T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	APUDY	N374057.88	W0871531.32	N3740.965	W08715.522
	CINLI	N375137.36	W0865819.96	N3751.623	W08658.333
	FOLAB	N373711.75	W0872133.88	N3737.196	W08721.565
	NASCI	N374237.19	W0871251.77	N3742.620	W08712.863
	RW06	N374409.72	W0871022.87	N3744.162	W08710.381

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	00405	45

CITY AND STATE
OWENSBORO, KY

ELEVATION: 407
AIRPORT NAME:
OWENSBORO-DAVIESS COUNTY

THRE: 405

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 6, AMDT 1

10 JANUARY 2013

SUP: RNAV (GPS) RWY 5

AMDT: ORIG

DATED: 09/30/2004