

Prae

U. S. Department of Transportation Federal Aviation Administration		ILS - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.29		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES				MISSED APPROACH												
FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: AT THE DH. 5.02 MILES AFTER												
SEA VORTAC	SCENN OM/INT	223.72/11.29	2000	SCENN OM/INT OR AT DME FIX.												
				CLIMB TO 1500, THEN CLIMBING RIGHT TURN TO 2000 VIA HEADING 290 AND SEA VORTAC R-224 TO SCENN INT AND HOLD.												
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 167 INBOUND. FAS OBST: 499 TREE 472113/1223343												
1. PT <u>L</u> SIDE OF COURSE <u>347</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF SCENN (IAF)																
2.																
3. FAC: <u>167.01</u> FAF: SCENN DIST FAF TO MAP: <u>5.02</u> THLD: <u>5.02</u>																
4. MIN. ALT: SCENN <u>2000</u>																
5. DIST TO THLD FROM OM: <u>5.02</u> MM: <u>0.44</u> IM: <u>150</u> HAT: <u>-</u> 100 HAT: <u>-</u> GS ANT: <u>827</u>																
6. MIN GS INCPT: <u>2000</u> GS ALT AT: <u>1964</u> OM: <u>1964</u> MM: <u>480</u> IM: <u>1964</u>																
7. GS ANGLE: <u>3.00</u> TCH: <u>52</u>																
8. MSA FROM: SEA VORTAC 010-160 6300, 160-250 2200, 250-010 3400																
				MAG VAR: 20E EPOCH YEAR: 90												
MINIMUMS																
TAKEOFF:		STANDARD ☒ SEE FAA FORM			ALTERNATE: N A		ILS: STANDARD #		LOC: STANDARD #							
CATEGORY =====>		A		B		C		D		E						
		DH/ MDA	VIS	DH/ MDA	VIS	HAT/ HAA	DH/ MDA	VIS	HAT/ HAA	DH/ MDA	VIS	HAT/ HAA	DH/ MDA	VIS	HAT/ HAA	
S - ILS 17		492	1/2	200	492	1/2	200	492	1/2	200	492	1/2	200			
S - LOC 17		760	1/2	488	760	1/2	488	760	3/4	488	760	1	488			
CIRCLING		760	1	488	760	1	488	760	1 1/2	488	860	2	568			
MCCHORD AFB ALTIMETER SETTING MINIMUMS																
S-ILS 17		517	1/2	225	517	1/2	225	517	1/2	225	517	1/2	225			
S-LOC 17		780	1/2	488	780	1/2	488	780	3/4	488	780	1	488			
CIRCLING		780	1	488	780	1	488	780	1 1/2	488	860	2	568			
NOTES: WHEN CONTROLTOWER CLOSED , OBTAIN LOCAL ALTIMETER SETTING ON UNICOM; WHEN NOT RECEIVED, # NA WHEN CONTROL TOWER CLOSED. USE MCCHORD AFB ALTIMETER SETTING MINIMUMS. CIRCLING NA E OF RWY 17-35																
CITY AND STATE		ELEVATION: 292 TDZE: 292		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:						
TACOMA, WA		TACOMA NARROWS		I-TIW		06 JAN 94 ILS RWY 17, AMDT 8				AMDT: 7						
										DATED 30 MAY 91						