

**Federal Aviation
Administration**

Transmittal Letter 20-21

August 21, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/8/2020	FL	St Augustine	Northeast Florida Rgnl	0/7828	8/4/2020	RNAV (GPS) RWY 13, Orig-E

AIRAC Date: 8 OCTOBER 2020

FDC 0/7828 SGJ IAP NORTHEAST FLORIDA RGNL, ST AUGUSTINE, FL. RNAV (GPS) RWY 13, ORIG-E... CHART CIRCLING ICON. CIRCLING CAT A MDA 520/HAA 510, CAT C MDA 660/HAA 650, CAT D MDA 780/HAA 770, VISIBILITY CAT C 1 3/4, CAT D 2 1/2. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JACKSONVILLE NAS (TOWERS FIELD) ALTIMETER SETTING; INCREASE ALL DA 57 FEET AND ALL MDA 60 FEET. INCREASE LPV AND LNAV/VNAV ALL CATS, LNAV CAT C AND CIRCLING CAT C/D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 13, ORIG-F. 2008031843-PERM