## Federal Aviation Administration

**Transmittal Letter 19-05** 

## January 11, 2019

# PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

#### The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
28-Feb-19	FL	Williston	Williston Muni	8/8062	1/8/19	RNAV (GPS) RWY 5, Orig-A

# AIRAC Date: 28 FEBRUARY 2019

FDC **8/8062** X60 IAP WILLISTON MUNI, Williston, FL. RNAV (GPS) RWY 5, ORIG-A... DELETE NOTE: NIGHT LANDING: RWY 5, 14, 23 NA. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHART NOTE: CIRCLING RWY 14, 32 NA AT NIGHT. CHART NOTE: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHART VDP AT 1.16 NM TO RW05. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OCALA ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CAT C 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OCALA ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET. THIS IS RNAV (GPS) RWY 5, ORIG-B. 1810221443-PERM